

Exceptions

Outline

- Exception Handling
- Precise and Imprecise exceptions
- Exceptions in OoO pipelines

Exceptions

**Events that request
attention of the processor**

Exceptions

- I/O device request

**Events that request
attention of the processor**

Exceptions

- I/O device request
- Invoking OS service from a user program

**Events that request
attention of the processor**

Exceptions

- I/O device request
- Invoking OS service from a user program
- Breakpoint (programmer-requested interrupt)

**Events that request
attention of the processor**

Exceptions

- I/O device request
- Invoking OS service from a user program
- Breakpoint (programmer-requested interrupt)
- Integer arithmetic overflow/FP arithmetic anomaly

**Events that request
attention of the processor**

Exceptions

- I/O device request
- Invoking OS service from a user program
- Breakpoint (programmer-requested interrupt)
- Integer arithmetic overflow/FP arithmetic anomaly
- Page fault

**Events that request
attention of the processor**

Exceptions

- I/O device request
- Invoking OS service from a user program
- Breakpoint (programmer-requested interrupt)
- Integer arithmetic overflow/FP arithmetic anomaly
- Page fault
- Undefined or unimplemented instruction


**Events that request
attention of the processor**

Exceptions


- I/O device request
- Invoking OS service from a user program
- Breakpoint (programmer-requested interrupt)
- Integer arithmetic overflow/FP arithmetic anomaly
- Page fault
- Undefined or unimplemented instruction
- Hardware malfunctions, Power failure

**Events that request
attention of the processor**


Exceptions



Precise Exception Handling



Precise Exceptions



- Instruction Status Vector: Check before *commit*

Exception Handling

Exception Handling

- Save the address of the offending instruction in the exception program counter (EPC)

Exception Handling

- Save the address of the offending instruction in the exception program counter (EPC)
- Transfer control to the operating system at some specified address.

Exception Handling

- Save the address of the offending instruction in the exception program counter (EPC)
- Transfer control to the operating system at some specified address.
- Handle the exception
 - Providing some service to the user program
 - Taking some predefined action in response to an overflow
 - Stopping the execution of the program and reporting an error


Exception Handling

- Save the address of the offending instruction in the exception program counter (EPC)
- Transfer control to the operating system at some specified address.
- Handle the exception
 - Providing some service to the user program
 - Taking some predefined action in response to an overflow
 - Stopping the execution of the program and reporting an error
- OS can terminate or may use EPC to restart program

Outline

- Exception Handling
- Precise and Imprecise exceptions
- Exceptions in OoO pipelines

Multi-cycle Operations Pipeline



Precise Exceptions

DIV.D	F0, F2, F4
ADD.D	F10, F10, F8
SUB.D	F12, F12, F14

- Out of order completion
- Can't ignore exceptions
 - Virtual Memory, IEEE 754
- Fast mode vs. Slow mode with precise exceptions
- Store results of earlier operations in a buffer
 - History file, Future file.

Stopping and Restarting Execution

- Trap instruction, Turn off writes, Save PC, Save processor state, (Disable Exceptions), Exception handler, RFE
- Precise exceptions

Pipeline stage	Problem exceptions occurring
IF	Page fault on IF, misaligned memory access; memory protection violation
ID	Undefined or illegal opcode
EX	Arithmetic exception
MEM	Page fault on data fetch; misaligned memory access; memory protection violation
WB	None

Precise Exceptions



- Multiple exceptions in the same cycle
- Early exception by a later instruction
- Instruction Status Vector: Check before *commit*