

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	GEMFI 600MG,STKF2A00
User ID :	sj97904	Batch NO. :	KFM2500260
Print Interval :	50000 Tablets	Running Time :	03 Hour 41 Min 41 Sec
Total Counter :	350068	Total Running Time :	3296 Hour 13 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	184	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		600000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.6	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.21	kN	No		
HEP :	25.0 %	9.82	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.01	kN	Yes 15	Times	
Ref :		7.86	kN			
LCP :	2.0 %	7.70	kN	Yes 15	Times	
LEP :	25.0 %	5.89	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.50	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.45	kN	Min :	1.28	kN	Punch NO.;	15
SD :	6.20	%	Max :	1.70	kN	Punch NO.;	49
Mean Main Pressure :	7.59	kN	Min :	6.82	kN	Punch NO.;	21
SD :	3.50	%	Max :	8.13	kN	Punch NO.;	17
Filling Depth :	Increase ;	283	Times	Decrease ;	266	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.90	mm	Pre Thickness ;	3.91	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.55	mm	Main Thickness ;	3.55	mm
Filling Depth :	8.74	mm	Current Cam :	Cam C	
Main Air pressure :	0.745	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	47	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.09	kN	Max Punch ;	10
Lower Punch :	Average ;	0.27	kN		
	Max ;	0.96	kN	Max Punch ;	49
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	350068	Tablets			
A.W.C Counter :	341726	Tablets			
HEP :	452 (0.1%)	Tablets	LEP :	361 (0.1%)	Tablets
GOOD :	340913 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	GEMFI 600MG,STKF2A00
User ID :	sj97904	Batch NO. :	KFM2500260
Print Interval :	50000 Tablets	Running Time :	03 Hour 41 Min 41 Sec
Total Counter :	350068	Total Running Time :	3296 Hour 13 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	152	%	Manual ;	45	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		600000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.6	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.31	kN	No		
HEP :	25.0 %	10.87	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.87	kN	Yes 15	Times	
Ref :		8.70	kN			
LCP :	2.0 %	8.52	kN	Yes 15	Times	
LEP :	25.0 %	6.52	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.09	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.03	kN	Min :	1.87	kN	Punch NO.;	15
SD :	4.90	%	Max :	2.37	kN	Punch NO.;	22
Mean Main Pressure :	8.75	kN	Min :	8.16	kN	Punch NO.;	4
SD :	2.80	%	Max :	9.33	kN	Punch NO.;	17
Filling Depth :	Increase ;	52	Times	Decrease ;	92	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	23	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.90	mm	Pre Thickness ;	3.91	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.60	mm	Main Thickness ;	3.61	mm
Filling Depth :	9.60	mm	Current Cam :	Cam C	
Main Air pressure :	0.745	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	47	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.09	kN	Max Punch ;	10
Lower Punch :	Average ;	0.27	kN		
	Max ;	0.94	kN	Max Punch ;	49
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	350068	Tablets			
A.W.C Counter :	341726	Tablets			
HEP :	452 (0.1%)	Tablets	LEP :	361 (0.1%)	Tablets
GOOD :	340913 (99.8%)	Tablets			