

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET BP500mg STMR2A00
User ID :	sj97904	Batch NO. :	MRM2504250
Print Interval :	50000 Tablets	Running Time :	00 Hour 59 Min 07 Sec
Total Counter :	150088	Total Running Time :	3299 Hour 42 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	112	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.6	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.69	kN	No		
HEP :	25.0 %	16.05	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.10	kN	Yes 15	Times	
Ref :		12.84	kN			
LCP :	2.0 %	12.58	kN	Yes 15	Times	
LEP :	25.0 %	9.63	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.99	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.21	kN	Min :	1.08	kN	Punch NO.;	33
SD :	5.00	%	Max :	1.36	kN	Punch NO.;	10
Mean Main Pressure :	12.79	kN	Min :	11.71	kN	Punch NO.;	33
SD :	2.80	%	Max :	13.68	kN	Punch NO.;	27
Filling Depth :	Increase ; 13	Times	Decrease ;	17	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.10	mm	Pre Thickness ;	3.11	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.90	mm	Main Thickness ;	2.91	mm
Filling Depth :	7.20	mm	Current Cam :	Cam C	
Main Air pressure :	0.743	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.18	kN	Max Punch ;	30
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	150088	Tablets			
A.W.C Counter :	144238	Tablets			
HEP :	297 (0.2%)	Tablets	LEP :	193 (0.1%)	Tablets
GOOD :	143748 (99.7%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET BP500mg STMR2A00
User ID :	sj97904	Batch NO. :	MRM2504250
Print Interval :	50000 Tablets	Running Time :	00 Hour 59 Min 07 Sec
Total Counter :	150088	Total Running Time :	3299 Hour 42 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	110	%	Manual ;	45	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.6	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.98	kN	No		
HEP :	25.0 %	18.25	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.89	kN	Yes 15	Times	
Ref :		14.60	kN			
LCP :	2.0 %	14.30	kN	Yes 15	Times	
LEP :	25.0 %	10.95	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.22	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.67	kN	Min :	1.54	kN	Punch NO.;	33
		2.90	%	Max :	1.79	kN	Punch NO.;	39
Mean Main Pressure :		14.48	kN	Min :	13.15	kN	Punch NO.;	31
	SD :	3.40	%	Max :	15.68	kN	Punch NO.;	39
Filling Depth :	Increase ;	20	Times	Decrease ;	16	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.20	mm	Pre Thickness ;	3.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.00	mm	Main Thickness ;	3.01	mm
Filling Depth :	6.96	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.743	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.20	kN	Max Punch ;	30
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	150088	Tablets			
A.W.C Counter :	144238	Tablets			
HEP :	297 (0.2%)	Tablets	LEP :	193 (0.1%)	Tablets
GOOD :	143748 (99.7%)	Tablets			