

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET BP500mg STMR2A00
User ID :	pb97604	Batch NO. :	MRM2504250
Print Interval :	50000 Tablets	Running Time :	07 Hour 53 Min 50 Sec
Total Counter :	1250516	Total Running Time :	3306 Hour 38 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	114	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.6	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.20	kN	No		
HEP :	25.0 %	14.62	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.93	kN	Yes 15	Times	
Ref :		11.70	kN			
LCP :	2.0 %	11.46	kN	Yes 15	Times	
LEP :	25.0 %	8.77	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.19	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.33	kN	Min :	1.20	kN	Punch NO.;	29
SD :	4.60	%	Max :	1.48	kN	Punch NO.;	35
Mean Main Pressure :	11.66	kN	Min :	11.14	kN	Punch NO.;	29
SD :	2.40	%	Max :	12.40	kN	Punch NO.;	34
Filling Depth :	Increase ; 58	Times	Decrease ;	81	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.10	mm	Pre Thickness ;	3.11	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.03	mm	Main Thickness ;	3.04	mm
Filling Depth :	7.15	mm	Current Cam :	Cam C	
Main Air pressure :	0.721	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.04	kN	Max Punch ;	28
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	11
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1250516	Tablets			
A.W.C Counter :	1243353	Tablets			
HEP :	317 (0.0%)	Tablets	LEP :	360 (0.0%)	Tablets
GOOD :	1242676 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET BP500mg STMR2A00
User ID :	pb97604	Batch NO. :	MRM2504250
Print Interval :	50000 Tablets	Running Time :	07 Hour 53 Min 50 Sec
Total Counter :	1250516	Total Running Time :	3306 Hour 38 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	118	%	Manual ;	45	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.6	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.59	kN	No		
HEP :	25.0 %	14.03	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.45	kN	Yes 15	Times	
Ref :		11.22	kN			
LCP :	2.0 %	11.00	kN	Yes 15	Times	
LEP :	25.0 %	8.42	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.86	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.62	kN	Min :	1.49	kN	Punch NO.;	14
		3.10	%	Max :	1.75	kN	Punch NO.;	35
Mean Main Pressure :		11.42	kN	Min :	10.56	kN	Punch NO.;	7
	SD :	3.10	%	Max :	12.32	kN	Punch NO.;	35
Filling Depth :	Increase ;	139	Times	Decrease ;	138	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.25	mm	Main Thickness ;	3.26	mm
Filling Depth :	7.02	mm	Current Cam :	Cam C	
Main Air pressure :	0.721	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	29
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	11
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1250516	Tablets			
A.W.C Counter :	1243353	Tablets			
HEP :	317 (0.0%)	Tablets	LEP :	360 (0.0%)	Tablets
GOOD :	1242676 (99.9%)	Tablets			