

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET BP500mg STMR2A00
User ID :	sj97904	Batch NO. :	MRM2504250
Print Interval :	50000 Tablets	Running Time :	21 Hour 32 Min 32 Sec
Total Counter :	3651574	Total Running Time :	3320 Hour 19 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	103	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.1	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.10	kN	No		
HEP :	25.0 %	15.48	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.63	kN	Yes 15	Times	
Ref :		12.38	kN			
LCP :	2.0 %	12.13	kN	Yes 15	Times	
LEP :	25.0 %	9.29	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.67	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.39	kN	Min :	1.28	kN	Punch NO.;	33
SD :	4.20	%	Max :	1.52	kN	Punch NO.;	2
Mean Main Pressure :	12.39	kN	Min :	11.73	kN	Punch NO.;	21
SD :	2.40	%	Max :	12.96	kN	Punch NO.;	53
Filling Depth :	Increase ; 128	Times	Decrease ;	154	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	29	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.10	mm	Pre Thickness ;	3.11	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.00	mm	Main Thickness ;	3.01	mm
Filling Depth :	7.50	mm	Current Cam :	Cam C	
Main Air pressure :	0.670	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.07	kN	Max Punch ;	15
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	38
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3651574	Tablets			
A.W.C Counter :	3643273	Tablets			
HEP :	328 (0.0%)	Tablets	LEP :	539 (0.0%)	Tablets
GOOD :	3642406 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET BP500mg STMR2A00
User ID :	sj97904	Batch NO. :	MRM2504250
Print Interval :	50000 Tablets	Running Time :	21 Hour 32 Min 32 Sec
Total Counter :	3651574	Total Running Time :	3320 Hour 19 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	101	%	Manual ;	45	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.1	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.94	kN	No		
HEP :	25.0 %	16.29	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.29	kN	Yes 15	Times	
Ref :		13.03	kN			
LCP :	2.0 %	12.77	kN	Yes 15	Times	
LEP :	25.0 %	9.78	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.12	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.78	kN	Min :	1.68	kN	Punch NO.;	11
SD :	3.20	%	Max :	1.91	kN	Punch NO.;	21
Mean Main Pressure :	12.91	kN	Min :	11.79	kN	Punch NO.;	11
SD :	3.60	%	Max :	13.85	kN	Punch NO.;	21
Filling Depth :	Increase ;	405	Times	Decrease ;	441	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.20	mm	Pre Thickness ;	3.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.16	mm	Main Thickness ;	3.17	mm
Filling Depth :	7.00	mm	Current Cam :	Cam C	
Main Air pressure :	0.670	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.07	kN	Max Punch ;	15
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	38
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3651574	Tablets			
A.W.C Counter :	3643273	Tablets			
HEP :	328 (0.0%)	Tablets	LEP :	539 (0.0%)	Tablets
GOOD :	3642406 (100.0%)	Tablets			