

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET BP500mg STMR2A00
User ID :	pb97604	Batch NO. :	MRM2504350
Print Interval :	50000 Tablets	Running Time :	02 Hour 14 Min 26 Sec
Total Counter :	400158	Total Running Time :	3327 Hour 11 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	103	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.1	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.70	kN	No		
HEP :	25.0 %	15.10	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.32	kN	Yes 15	Times	
Ref :		12.08	kN			
LCP :	2.0 %	11.84	kN	Yes 15	Times	
LEP :	25.0 %	9.06	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.46	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.32	kN	Min :	1.21	kN	Punch NO.;	51
SD :	4.30	%	Max :	1.49	kN	Punch NO.;	27
Mean Main Pressure :	12.00	kN	Min :	11.32	kN	Punch NO.;	5
SD :	2.80	%	Max :	13.04	kN	Punch NO.;	27
Filling Depth :	Increase ;	227	Times	Decrease ;	244	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	29	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.10	mm	Pre Thickness ;	3.11	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.00	mm	Main Thickness ;	3.01	mm
Filling Depth :	7.16	mm	Current Cam :	Cam C	
Main Air pressure :	0.768	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.10	kN	Max Punch ;	11
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	23
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	400158	Tablets			
A.W.C Counter :	398030	Tablets			
HEP :	25 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	398005 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET BP500mg STMR2A00
User ID :	pb97604	Batch NO. :	MRM2504350
Print Interval :	50000 Tablets	Running Time :	02 Hour 14 Min 26 Sec
Total Counter :	400158	Total Running Time :	3327 Hour 11 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	96	%	Manual ;	45	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.1	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.83	kN	No		
HEP :	25.0 %	16.18	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.20	kN	Yes 15	Times	
Ref :		12.94	kN			
LCP :	2.0 %	12.69	kN	Yes 15	Times	
LEP :	25.0 %	9.71	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.06	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.79	kN	Min :	1.64	kN	Punch NO.;	23
SD :	3.60	%	Max :	1.92	kN	Punch NO.;	47
Mean Main Pressure :	12.92	kN	Min :	11.65	kN	Punch NO.;	23
SD :	3.90	%	Max :	13.89	kN	Punch NO.;	34
Filling Depth :	Increase ;	670	Times	Decrease ;	700	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	27	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.20	mm	Pre Thickness ;	3.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.16	mm	Main Thickness ;	3.17	mm
Filling Depth :	7.12	mm	Current Cam :	Cam C	
Main Air pressure :	0.768	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.12	kN	Max Punch ;	9
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	23
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	400158	Tablets			
A.W.C Counter :	398030	Tablets			
HEP :	25 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	398005 (100.0%)	Tablets			