

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET BP500mg STMR2A00
User ID :	sj97904	Batch NO. :	MRM2504350
Print Interval :	50000 Tablets	Running Time :	15 Hour 07 Min 09 Sec
Total Counter :	2701132	Total Running Time :	3340 Hour 5 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	107	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.1	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.74	kN	No		
HEP :	25.0 %	15.13	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	12.35	kN	Yes	15	Times
Ref :		12.11	kN			
LCP :	2.0 %	11.86	kN	Yes	15	Times
LEP :	25.0 %	9.08	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	8.47	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.34	kN	Min :	1.22	kN	Punch NO.;	17
SD :	4.80	%	Max :	1.61	kN	Punch NO.;	38
Mean Main Pressure :	12.03	kN	Min :	11.19	kN	Punch NO.;	33
SD :	3.30	%	Max :	13.35	kN	Punch NO.;	38
Filling Depth :	Increase ;	459	Times	Decrease ;	470	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.10	mm	Pre Thickness ;	3.11	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.05	mm	Main Thickness ;	3.06	mm
Filling Depth :	7.11	mm	Current Cam :	Cam C	
Main Air pressure :	0.762	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	42	Min			
Lower Punch Remain Time (S2):	25	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.07	kN	Max Punch ;	29
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	38
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2701132	Tablets			
A.W.C Counter :	2697980	Tablets			
HEP :	210 (0.0%)	Tablets	LEP :	739 (0.0%)	Tablets
GOOD :	2697031 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET BP500mg STMR2A00
User ID :	sj97904	Batch NO. :	MRM2504350
Print Interval :	50000 Tablets	Running Time :	15 Hour 07 Min 09 Sec
Total Counter :	2701132	Total Running Time :	3340 Hour 5 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	106	%	Manual ;	45	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.1	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.49	kN	No		
HEP :	25.0 %	15.86	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.94	kN	Yes 15	Times	
Ref :		12.69	kN			
LCP :	2.0 %	12.43	kN	Yes 15	Times	
LEP :	25.0 %	9.52	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.88	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.76	kN	Min :	1.64	kN	Punch NO.;	2
SD :	3.50	%	Max :	1.91	kN	Punch NO.;	34
Mean Main Pressure :	12.47	kN	Min :	11.06	kN	Punch NO.;	36
SD :	4.10	%	Max :	13.65	kN	Punch NO.;	21
Filling Depth :	Increase ;	1722	Times	Decrease ;	1748	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.20	mm	Pre Thickness ;	3.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.19	mm	Main Thickness ;	3.20	mm
Filling Depth :	7.10	mm	Current Cam :	Cam C	
Main Air pressure :	0.762	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	42	Min			
Lower Punch Remain Time (S2):	25	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.05	kN	Max Punch ;	29
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	38
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2701132	Tablets			
A.W.C Counter :	2697980	Tablets			
HEP :	210 (0.0%)	Tablets	LEP :	739 (0.0%)	Tablets
GOOD :	2697031 (100.0%)	Tablets			