

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 750MG STHA1B00
User ID :	mk98268	Batch NO. :	HAM2401075
Print Interval :	50000 Tablets	Running Time :	02 Hour 38 Min 13 Sec
Total Counter :	250052	Total Running Time :	321 Hour 25 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	255	%	Manual ;	45	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		500000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.27	kN	No		
HEP :	25.0 %	10.84	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.84	kN	Yes 15	Times	
Ref :		8.67	kN			
LCP :	2.0 %	8.50	kN	Yes 15	Times	
LEP :	25.0 %	6.50	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.07	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.90	kN	Min :	1.82	kN	Punch NO.;	17
SD :	2.30	%	Max :	1.99	kN	Punch NO.;	11
Mean Main Pressure :	8.66	kN	Min :	8.23	kN	Punch NO.;	26
SD :	2.70	%	Max :	9.19	kN	Punch NO.;	51
Filling Depth :	Increase ;	1583	Times	Decrease ;	1346	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	38	RPM
Pre Upper Punch Position ;	2.49	mm			
Pre Lower Punch Position ;	7.80	mm	Pre Thickness ;	5.31	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.55	mm	Main Thickness ;	3.05	mm
Filling Depth :	9.62	mm	Current Cam :	Cam C	
Main Air pressure :	0.826	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.27	kN	Max Punch ;	33
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.18	kN	Max Punch ;	24
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	15

Tablet Data (N/A)

Total Counter :	250052	Tablets			
A.W.C Counter :	248517	Tablets			
HEP :	3 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	248513 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 750MG STHA1B00
User ID :	mk98268	Batch NO. :	HAM2401075
Print Interval :	50000 Tablets	Running Time :	02 Hour 38 Min 13 Sec
Total Counter :	250052	Total Running Time :	321 Hour 25 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	255	%	Manual ;	59	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		500000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.64	kN	No		
HEP :	25.0 %	12.16	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.92	kN	Yes 15	Times	
Ref :		9.73	kN			
LCP :	2.0 %	9.53	kN	Yes 15	Times	
LEP :	25.0 %	7.30	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.81	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.91	kN	Min :	1.82	kN	Punch NO.;	24
SD :	2.10	%	Max :	2.00	kN	Punch NO.;	53
Mean Main Pressure :	9.65	kN	Min :	8.75	kN	Punch NO.;	24
SD :	3.80	%	Max :	10.40	kN	Punch NO.;	41
Filling Depth :	Increase ;	1417	Times	Decrease ;	1274	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	38	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	7.80	mm	Pre Thickness ;	5.30	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.55	mm	Main Thickness ;	3.05	mm
Filling Depth :	9.68	mm	Current Cam :	Cam C	
Main Air pressure :	0.826	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.26	kN	Max Punch ;	33
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.18	kN	Max Punch ;	24
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	15

Tablet Data (N/A)

Total Counter :	250052	Tablets			
A.W.C Counter :	248517	Tablets			
HEP :	3 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	248513 (100.0%)	Tablets			