

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 750MG STHA1B00
User ID :	mk98268	Batch NO. :	HAM2401075
Print Interval :	50000 Tablets	Running Time :	03 Hour 31 Min 08 Sec
Total Counter :	333730	Total Running Time :	322 Hour 18 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	255	%	Manual ;	45	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		500000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.27	kN	No		
HEP :	25.0 %	10.84	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.84	kN	Yes 15	Times	
Ref :		8.67	kN			
LCP :	2.0 %	8.50	kN	Yes 15	Times	
LEP :	25.0 %	6.50	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.07	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.89	kN	Min :	1.80	kN	Punch NO.;	9
SD :	2.20	%	Max :	1.96	kN	Punch NO.;	6
Mean Main Pressure :	8.66	kN	Min :	8.25	kN	Punch NO.;	42
SD :	2.60	%	Max :	9.19	kN	Punch NO.;	13
Filling Depth :	Increase ;	1585	Times	Decrease ;	1350	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	38	RPM
Pre Upper Punch Position ;	2.49	mm			
Pre Lower Punch Position ;	7.80	mm	Pre Thickness ;	5.31	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.55	mm	Main Thickness ;	3.05	mm
Filling Depth :	9.56	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.822	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	47	Min			
Lower Punch Remain Time (S2):	39	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.26	kN	Max Punch ;	33
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.18	kN	Max Punch ;	24
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	15

Tablet Data (N/A)

Total Counter :	333730	Tablets			
A.W.C Counter :	332204	Tablets			
HEP :	3 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	332200 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 750MG STHA1B00
User ID :	mk98268	Batch NO. :	HAM2401075
Print Interval :	50000 Tablets	Running Time :	03 Hour 31 Min 08 Sec
Total Counter :	333730	Total Running Time :	322 Hour 18 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	255	%	Manual ;	59	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		500000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.64	kN	No		
HEP :	25.0 %	12.16	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.92	kN	Yes 15	Times	
Ref :		9.73	kN			
LCP :	2.0 %	9.53	kN	Yes 15	Times	
LEP :	25.0 %	7.30	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.81	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.91	kN	Min :	1.81	kN	Punch NO.;	9
SD :	2.60	%	Max :	2.05	kN	Punch NO.;	37
Mean Main Pressure :	9.71	kN	Min :	8.87	kN	Punch NO.;	31
SD :	4.70	%	Max :	10.93	kN	Punch NO.;	39
Filling Depth :	Increase ;	1420	Times	Decrease ;	1277	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	38	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	7.80	mm	Pre Thickness ;	5.30	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.55	mm	Main Thickness ;	3.05	mm
Filling Depth :	9.68	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.822	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	47	Min			
Lower Punch Remain Time (S2):	39	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.26	kN	Max Punch ;	33
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.18	kN	Max Punch ;	9
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	15

Tablet Data (N/A)

Total Counter :	333730	Tablets			
A.W.C Counter :	332204	Tablets			
HEP :	3 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	332200 (100.0%)	Tablets			