

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MGSTVI1A00
User ID :	ka89411	Batch NO. :	VIM2401820
Print Interval :	50000 Tablets	Running Time :	01 Hour 48 Min 11 Sec
Total Counter :	300672	Total Running Time :	325 Hour 47 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	75	%	Manual ;	45	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1740000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.86	kN	No		
HEP :	25.0 %	12.37	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	10.09	kN	Yes 10	Times	
Ref :		9.89	kN			
LCP :	2.0 %	9.70	kN	Yes 10	Times	
LEP :	25.0 %	7.42	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	6.93	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.71	kN	Min :	0.69	kN	Punch NO.;	38
SD :	1.70	%	Max :	0.75	kN	Punch NO.;	37
Mean Main Pressure :	10.06	kN	Min :	9.54	kN	Punch NO.;	19
SD :	2.20	%	Max :	10.53	kN	Punch NO.;	45
Filling Depth :	Increase ;	4	Times	Decrease ;	8	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	7.20	mm	Pre Thickness ;	4.70	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.90	mm	Main Thickness ;	1.40	mm
Filling Depth :	5.67	mm	Current Cam :	Cam B	
Main Air pressure :	0.817	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	32	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	28
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	8
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.07	kN	Max Punch ;	50

Tablet Data (N/A)

Total Counter :	300672	Tablets			
A.W.C Counter :	286333	Tablets			
HEP :	454 (0.2%)	Tablets	LEP :	356 (0.1%)	Tablets
GOOD :	285523 (99.7%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MGSTVI1A0 0
User ID :	ka89411	Batch NO. :	VIM2401820
Print Interval :	50000 Tablets	Running Time :	01 Hour 48 Min 11 Sec
Total Counter :	300672	Total Running Time :	325 Hour 47 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	75	%	Manual ;	59	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1740000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.51	kN	No		
HEP :	25.0 %	12.99	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	10.60	kN	Yes	10 Times	
Ref :		10.39	kN			
LCP :	2.0 %	10.19	kN	Yes	10 Times	
LEP :	25.0 %	7.80	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	7.28	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.88	kN	Min :	0.85	kN	Punch NO.;	31
SD :	1.30	%	Max :	0.91	kN	Punch NO.;	12
Mean Main Pressure :	10.47	kN	Min :	9.69	kN	Punch NO.;	9
SD :	3.00	%	Max :	11.39	kN	Punch NO.;	61
Filling Depth :	Increase ;	7	Times	Decrease ;	7	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	7.40	mm	Pre Thickness ;	4.90	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.93	mm	Main Thickness ;	1.43	mm
Filling Depth :	5.96	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.817	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	32	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.07	kN	Max Punch ;	56
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	8
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.07	kN	Max Punch ;	50

Tablet Data (N/A)

Total Counter :	300672	Tablets			
A.W.C Counter :	286333	Tablets			
HEP :	454 (0.2%)	Tablets	LEP :	356 (0.1%)	Tablets
GOOD :	285523 (99.7%)	Tablets			