

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MGSTVI1A00
User ID :	vg96371	Batch NO. :	VIM2401820
Print Interval :	50000 Tablets	Running Time :	04 Hour 08 Min 29 Sec
Total Counter :	756302	Total Running Time :	328 Hour 8 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	76	%	Manual ;	45	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1740000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.48	kN	No		
HEP :	25.0 %	12.96	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	10.57	kN	Yes 10	Times	
Ref :		10.37	kN			
LCP :	2.0 %	10.16	kN	Yes 10	Times	
LEP :	25.0 %	7.78	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	7.26	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.63	kN	Min :	0.61	kN	Punch NO.;	46
SD :	1.80	%	Max :	0.66	kN	Punch NO.;	13
Mean Main Pressure :	10.35	kN	Min :	9.80	kN	Punch NO.;	23
SD :	2.00	%	Max :	11.00	kN	Punch NO.;	49
Filling Depth :	Increase ; 1	Times	Decrease ;	15	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	7.19	mm	Pre Thickness ;	4.69	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.90	mm	Main Thickness ;	1.40	mm
Filling Depth :	5.67	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.801	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.05	kN	Max Punch ;	9
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	5
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	25

Tablet Data (N/A)

Total Counter :	756302	Tablets			
A.W.C Counter :	741076	Tablets			
HEP :	454 (0.1%)	Tablets	LEP :	356 (0.0%)	Tablets
GOOD :	740266 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MGSTVI1A00
User ID :	vg96371	Batch NO. :	VIM2401820
Print Interval :	50000 Tablets	Running Time :	04 Hour 08 Min 29 Sec
Total Counter :	756302	Total Running Time :	328 Hour 8 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	75	%	Manual ;	59	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1740000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.05	kN	No		
HEP :	25.0 %	13.51	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	11.03	kN	Yes	10 Times	
Ref :		10.81	kN			
LCP :	2.0 %	10.59	kN	Yes	10 Times	
LEP :	25.0 %	8.11	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	7.57	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.78	kN	Min :	0.76	kN	Punch NO.;	41
SD :	1.70	%	Max :	0.82	kN	Punch NO.;	56
Mean Main Pressure :	10.78	kN	Min :	10.22	kN	Punch NO.;	19
SD :	2.50	%	Max :	11.49	kN	Punch NO.;	43
Filling Depth :	Increase ;	6	Times	Decrease ;	8	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	7.39	mm	Pre Thickness ;	4.89	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.93	mm	Main Thickness ;	1.43	mm
Filling Depth :	5.97	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.801	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.05	kN	Max Punch ;	9
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.15	kN	Max Punch ;	5
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	54

Tablet Data (N/A)

Total Counter :	756302	Tablets			
A.W.C Counter :	741141	Tablets			
HEP :	454 (0.1%)	Tablets	LEP :	356 (0.0%)	Tablets
GOOD :	740331 (99.9%)	Tablets			