

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MGSTVI1A00
User ID :	pb97604	Batch NO. :	VIM2401820
Print Interval :	50000 Tablets	Running Time :	09 Hour 27 Min 01 Sec
Total Counter :	1606728	Total Running Time :	333 Hour 26 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	76	%	Manual ;	45	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1740000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.42	kN	No		
HEP :	25.0 %	12.91	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	10.53	kN	Yes 10	Times	
Ref :		10.33	kN			
LCP :	2.0 %	10.12	kN	Yes 10	Times	
LEP :	25.0 %	7.74	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	7.23	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.65	kN	Min :	0.63	kN	Punch NO.;	19
SD :	1.70	%	Max :	0.67	kN	Punch NO.;	49
Mean Main Pressure :	10.28	kN	Min :	9.78	kN	Punch NO.;	18
SD :	2.00	%	Max :	10.69	kN	Punch NO.;	31
Filling Depth :	Increase ;	15	Times	Decrease ;	21	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	7.19	mm	Pre Thickness ;	4.69	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.90	mm	Main Thickness ;	1.40	mm
Filling Depth :	5.73	mm	Current Cam :	Cam B	
Main Air pressure :	0.819	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	60	Min			
Lower Punch Remain Time (S2):	32	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.07	kN	Max Punch ;	16
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	65
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	55

Tablet Data (N/A)

Total Counter :	1606728	Tablets			
A.W.C Counter :	1586143	Tablets			
HEP :	513 (0.0%)	Tablets	LEP :	562 (0.0%)	Tablets
GOOD :	1585068 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MGSTVI1A0 0
User ID :	pb97604	Batch NO. :	VIM2401820
Print Interval :	50000 Tablets	Running Time :	09 Hour 27 Min 01 Sec
Total Counter :	1606728	Total Running Time :	333 Hour 26 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	75	%	Manual ;	59	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1740000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.05	kN	No		
HEP :	25.0 %	13.51	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	11.03	kN	Yes	10 Times	
Ref :		10.81	kN			
LCP :	2.0 %	10.59	kN	Yes	10 Times	
LEP :	25.0 %	8.11	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	7.57	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.76	kN	Min :	0.72	kN	Punch NO.;	45
SD :	1.70	%	Max :	0.79	kN	Punch NO.;	10
Mean Main Pressure :	10.80	kN	Min :	10.27	kN	Punch NO.;	2
SD :	2.30	%	Max :	11.52	kN	Punch NO.;	64
Filling Depth :	Increase ;	17	Times	Decrease ;	22	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	7.39	mm	Pre Thickness ;	4.89	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.93	mm	Main Thickness ;	1.43	mm
Filling Depth :	5.92	mm	Current Cam :	Cam B	
Main Air pressure :	0.819	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	60	Min			
Lower Punch Remain Time (S2):	32	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.07	kN	Max Punch ;	16
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	21
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	1606728	Tablets			
A.W.C Counter :	1586143	Tablets			
HEP :	513 (0.0%)	Tablets	LEP :	562 (0.0%)	Tablets
GOOD :	1585068 (99.9%)	Tablets			