

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	pb97604	Batch NO. :	VIM2402440
Print Interval :	50000 Tablets	Running Time :	00 Hour 25 Min 56 Sec
Total Counter :	50032	Total Running Time :	334 Hour 33 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	68	%	Manual ;	45	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.98	kN	No		
HEP :	25.0 %	17.28	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	14.10	kN	Yes	10 Times	
Ref :		13.83	kN			
LCP :	2.0 %	13.55	kN	Yes	10 Times	
LEP :	25.0 %	10.37	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	9.68	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.43	kN	Min :	2.33	kN	Punch NO.;	58
SD :	1.60	%	Max :	2.52	kN	Punch NO.;	17
Mean Main Pressure :	13.86	kN	Min :	13.37	kN	Punch NO.;	13
SD :	1.50	%	Max :	14.29	kN	Punch NO.;	50
Filling Depth :	Increase ;	0	Times	Decrease ;	0	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	117000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.44	mm	Main Thickness ;	1.94	mm
Filling Depth :	7.36	mm	Current Cam :	Cam C	
Main Air pressure :	0.698	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	38	Min			
Lower Punch Remain Time (S2):	40	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	25
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	42
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.05	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	50032	Tablets			
A.W.C Counter :	38102	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	38102 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	pb97604	Batch NO. :	VIM2402440
Print Interval :	50000 Tablets	Running Time :	00 Hour 25 Min 56 Sec
Total Counter :	50032	Total Running Time :	334 Hour 33 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	68	%	Manual ;	59	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.96	kN	No		
HEP :	25.0 %	17.27	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.09	kN	Yes 10	Times	
Ref :		13.81	kN			
LCP :	2.0 %	13.54	kN	Yes 10	Times	
LEP :	25.0 %	10.36	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.67	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.30	kN	Min :	2.21	kN	Punch NO.;	19
SD :	2.10	%	Max :	2.42	kN	Punch NO.;	53
Mean Main Pressure :	13.90	kN	Min :	13.40	kN	Punch NO.;	8
SD :	1.70	%	Max :	14.51	kN	Punch NO.;	46
Filling Depth :	Increase ;	0	Times	Decrease ;	0	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	117000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.52	mm	Main Thickness ;	2.02	mm
Filling Depth :	7.70	mm	Current Cam :	Cam C	
Main Air pressure :	0.698	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	38	Min			
Lower Punch Remain Time (S2):	40	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	31
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	42
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.05	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	50032	Tablets			
A.W.C Counter :	38102	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	38102 (100.0%)	Tablets			