

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	ka89411	Batch NO. :	VIM2402440
Print Interval :	50000 Tablets	Running Time :	02 Hour 33 Min 58 Sec
Total Counter :	450186	Total Running Time :	336 Hour 41 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	45	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.62	kN	No		
HEP :	25.0 %	17.90	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	14.61	kN	Yes	10 Times	
Ref :		14.32	kN			
LCP :	2.0 %	14.04	kN	Yes	10 Times	
LEP :	25.0 %	10.74	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	10.03	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.45	kN	Min :	2.39	kN	Punch NO.;	10
SD :	1.20	%	Max :	2.51	kN	Punch NO.;	27
Mean Main Pressure :	14.37	kN	Min :	13.82	kN	Punch NO.;	3
SD :	1.60	%	Max :	14.95	kN	Punch NO.;	46
Filling Depth :	Increase ;	14	Times	Decrease ;	11	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.44	mm	Main Thickness ;	1.94	mm
Filling Depth :	7.72	mm	Current Cam :	Cam C	
Main Air pressure :	0.807	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	38	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.05	kN	Max Punch ;	17
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.16	kN	Max Punch ;	33
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	55

Tablet Data (N/A)

Total Counter :	450186	Tablets			
A.W.C Counter :	429648	Tablets			
HEP :	0 (0%)	Tablets	LEP :	4 (0.0%)	Tablets
GOOD :	429644 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	ka89411	Batch NO. :	VIM2402440
Print Interval :	50000 Tablets	Running Time :	02 Hour 33 Min 58 Sec
Total Counter :	450186	Total Running Time :	336 Hour 41 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	59	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.61	kN	No		
HEP :	25.0 %	17.89	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.60	kN	Yes 10	Times	
Ref :		14.31	kN			
LCP :	2.0 %	14.03	kN	Yes 10	Times	
LEP :	25.0 %	10.74	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.02	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.27	kN	Min :	2.14	kN	Punch NO.;	24
SD :	2.20	%	Max :	2.37	kN	Punch NO.;	53
Mean Main Pressure :	14.43	kN	Min :	13.85	kN	Punch NO.;	9
SD :	1.50	%	Max :	14.99	kN	Punch NO.;	46
Filling Depth :	Increase ;	6	Times	Decrease ;	5	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.52	mm	Main Thickness ;	2.02	mm
Filling Depth :	7.61	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.807	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	38	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.05	kN	Max Punch ;	17
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.16	kN	Max Punch ;	33
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	55

Tablet Data (N/A)

Total Counter :	450186	Tablets			
A.W.C Counter :	429648	Tablets			
HEP :	0 (0%)	Tablets	LEP :	4 (0.0%)	Tablets
GOOD :	429644 (100.0%)	Tablets			