

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	ka89411	Batch NO. :	VIM2402440
Print Interval :	50000 Tablets	Running Time :	08 Hour 17 Min 25 Sec
Total Counter :	1400626	Total Running Time :	342 Hour 25 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	45	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.73	kN	No		
HEP :	25.0 %	18.01	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.70	kN	Yes 10	Times	
Ref :		14.41	kN			
LCP :	2.0 %	14.12	kN	Yes 10	Times	
LEP :	25.0 %	10.81	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.09	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.44	kN	Min :	2.36	kN	Punch NO.;	19
SD :	1.20	%	Max :	2.51	kN	Punch NO.;	1
Mean Main Pressure :	15.23	kN	Min :	14.66	kN	Punch NO.;	48
SD :	1.60	%	Max :	15.97	kN	Punch NO.;	30
Filling Depth :	Increase ; 26	Times	Decrease ; 41	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.44	mm	Main Thickness ;	1.94	mm
Filling Depth :	7.47	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.851	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	56	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.11	kN	Max Punch ;	14
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	33
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	38

Tablet Data (N/A)

Total Counter :	1400626	Tablets			
A.W.C Counter :	1377379	Tablets			
HEP :	78 (0.0%)	Tablets	LEP :	153 (0.0%)	Tablets
GOOD :	1377148 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	ka89411	Batch NO. :	VIM2402440
Print Interval :	50000 Tablets	Running Time :	08 Hour 17 Min 25 Sec
Total Counter :	1400626	Total Running Time :	342 Hour 25 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	59	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.78	kN	No		
HEP :	25.0 %	18.06	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.74	kN	Yes 10	Times	
Ref :		14.45	kN			
LCP :	2.0 %	14.16	kN	Yes 10	Times	
LEP :	25.0 %	10.83	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.11	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.31	kN	Min :	2.25	kN	Punch NO.;	6
SD :	1.00	%	Max :	2.37	kN	Punch NO.;	1
Mean Main Pressure :	14.55	kN	Min :	13.84	kN	Punch NO.;	24
SD :	1.70	%	Max :	15.09	kN	Punch NO.;	60
Filling Depth :	Increase ;	9	Times	Decrease ;	12	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.52	mm	Main Thickness ;	2.02	mm
Filling Depth :	7.57	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.851	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	56	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.11	kN	Max Punch ;	14
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	37
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	38

Tablet Data (N/A)

Total Counter :	1400626	Tablets			
A.W.C Counter :	1377379	Tablets			
HEP :	78 (0.0%)	Tablets	LEP :	153 (0.0%)	Tablets
GOOD :	1377148 (100.0%)	Tablets			