

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MG STV11A00
User ID :	pb97604	Batch NO. :	VIM2500120
Print Interval :	50000 Tablets	Running Time :	01 Hour 15 Min 29 Sec
Total Counter :	200114	Total Running Time :	344 Hour 19 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	70	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1740000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.71	kN	No		
HEP :	25.0 %	12.23	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	9.98	kN	Yes	10 Times	
Ref :		9.78	kN			
LCP :	2.0 %	9.59	kN	Yes	10 Times	
LEP :	25.0 %	7.34	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	6.85	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	0.99	kN	Min :	0.97	kN	Punch NO.;	48
		1.10	%	Max :	1.03	kN	Punch NO.;	65
Mean Main Pressure :		9.80	kN	Min :	9.38	kN	Punch NO.;	47
	SD :	2.10	%	Max :	10.34	kN	Punch NO.;	38
Filling Depth :	Increase ;	4	Times	Decrease ;	3	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.90	mm	Pre Thickness ;	4.40	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.90	mm	Main Thickness ;	1.40	mm
Filling Depth :	5.77	mm	Current Cam :	Cam B	
Main Air pressure :	0.802	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.09	kN	Max Punch ;	8
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	5
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	54

Tablet Data (N/A)

Total Counter :	200114	Tablets			
A.W.C Counter :	189449	Tablets			
HEP :	0 (0%)	Tablets	LEP :	464 (0.2%)	Tablets
GOOD :	188985 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MG STV11A00
User ID :	pb97604	Batch NO. :	VIM2500120
Print Interval :	50000 Tablets	Running Time :	01 Hour 15 Min 29 Sec
Total Counter :	200114	Total Running Time :	344 Hour 19 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	70	%	Manual ;	59	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1740000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		90	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.22	kN	No		
HEP :	25.0 %	12.71	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	10.37	kN	Yes	10 Times	
Ref :		10.17	kN			
LCP :	2.0 %	9.97	kN	Yes	10 Times	
LEP :	25.0 %	7.63	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	7.12	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.11	kN	Min :	1.08	kN	Punch NO.;	45
SD :	1.40	%	Max :	1.15	kN	Punch NO.;	4
Mean Main Pressure :	10.16	kN	Min :	9.69	kN	Punch NO.;	14
SD :	2.10	%	Max :	10.58	kN	Punch NO.;	65
Filling Depth :	Increase ;	5	Times	Decrease ;	10	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	7.10	mm	Pre Thickness ;	4.60	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.94	mm	Main Thickness ;	1.44	mm
Filling Depth :	5.75	mm	Current Cam :	Cam B	
Main Air pressure :	0.802	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.09	kN	Max Punch ;	8
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	2
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	50

Tablet Data (N/A)

Total Counter :	200114	Tablets			
A.W.C Counter :	189449	Tablets			
HEP :	0 (0%)	Tablets	LEP :	464 (0.2%)	Tablets
GOOD :	188985 (99.8%)	Tablets			