

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MG STV11A00
User ID :	ka89411	Batch NO. :	VIM2500120
Print Interval :	50000 Tablets	Running Time :	10 Hour 01 Min 49 Sec
Total Counter :	1703484	Total Running Time :	353 Hour 6 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	73	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1740000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.98	kN	No		
HEP :	25.0 %	12.48	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	10.19	kN	Yes 10	Times	
Ref :		9.99	kN			
LCP :	2.0 %	9.79	kN	Yes 10	Times	
LEP :	25.0 %	7.49	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	6.99	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.93	kN	Min :	0.91	kN	Punch NO.;	19
SD :	1.00	%	Max :	0.95	kN	Punch NO.;	29
Mean Main Pressure :	9.91	kN	Min :	9.43	kN	Punch NO.;	19
SD :	2.10	%	Max :	10.39	kN	Punch NO.;	31
Filling Depth :	Increase ; 4	Times	Decrease ;	14	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.90	mm	Pre Thickness ;	4.40	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.90	mm	Main Thickness ;	1.40	mm
Filling Depth :	5.60	mm	Current Cam :	Cam B	
Main Air pressure :	0.799	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	49	Min			
Lower Punch Remain Time (S2):	31	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.11	kN	Max Punch ;	48
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	1
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	31

Tablet Data (N/A)

Total Counter :	1703484	Tablets			
A.W.C Counter :	1685181	Tablets			
HEP :	0 (0%)	Tablets	LEP :	464 (0.0%)	Tablets
GOOD :	1684717 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MG STV11A00
User ID :	ka89411	Batch NO. :	VIM2500120
Print Interval :	50000 Tablets	Running Time :	10 Hour 01 Min 49 Sec
Total Counter :	1703484	Total Running Time :	353 Hour 6 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	73	%	Manual ;	59	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1740000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.78	kN	No		
HEP :	25.0 %	13.25	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	10.81	kN	Yes	10 Times	
Ref :		10.60	kN			
LCP :	2.0 %	10.39	kN	Yes	10 Times	
LEP :	25.0 %	7.95	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	7.42	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.03	kN	Min :	1.00	kN	Punch NO.;	50
		1.10	%	Max :	1.05	kN	Punch NO.;	5
Mean Main Pressure :	SD :	10.45	kN	Min :	9.88	kN	Punch NO.;	9
		2.80	%	Max :	11.30	kN	Punch NO.;	38
Filling Depth :	Increase ;	11	Times	Decrease ;	22	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	7.10	mm	Pre Thickness ;	4.60	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.94	mm	Main Thickness ;	1.44	mm
Filling Depth :	5.91	mm	Current Cam :	Cam B	
Main Air pressure :	0.799	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	49	Min			
Lower Punch Remain Time (S2):	31	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.11	kN	Max Punch ;	48
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	16
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	4

Tablet Data (N/A)

Total Counter :	1703484	Tablets			
A.W.C Counter :	1685181	Tablets			
HEP :	0 (0%)	Tablets	LEP :	464 (0.0%)	Tablets
GOOD :	1684717 (100.0%)	Tablets			