

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	pb97604	Batch NO. :	VIM2500140
Print Interval :	50000 Tablets	Running Time :	00 Hour 59 Min 30 Sec
Total Counter :	150094	Total Running Time :	364 Hour 23 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	45	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.27	kN	No		
HEP :	25.0 %	18.53	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	15.12	kN	Yes	10 Times	
Ref :		14.83	kN			
LCP :	2.0 %	14.53	kN	Yes	10 Times	
LEP :	25.0 %	11.12	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	10.38	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.54	kN	Min :	2.48	kN	Punch NO.;	3
SD :	1.50	%	Max :	2.64	kN	Punch NO.;	36
Mean Main Pressure :	14.92	kN	Min :	14.34	kN	Punch NO.;	14
SD :	1.70	%	Max :	15.54	kN	Punch NO.;	32
Filling Depth :	Increase ;	4	Times	Decrease ;	11	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.44	mm	Main Thickness ;	1.94	mm
Filling Depth :	7.25	mm	Current Cam :	Cam C	
Main Air pressure :	0.823	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	33	Min			
Lower Punch Remain Time (S2):	35	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.04	kN	Max Punch ;	49
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.17	kN	Max Punch ;	46
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	150094	Tablets			
A.W.C Counter :	140891	Tablets			
HEP :	43 (0.0%)	Tablets	LEP :	125 (0.1%)	Tablets
GOOD :	140723 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	pb97604	Batch NO. :	VIM2500140
Print Interval :	50000 Tablets	Running Time :	00 Hour 59 Min 30 Sec
Total Counter :	150094	Total Running Time :	364 Hour 23 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	59	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.18	kN	No		
HEP :	25.0 %	18.44	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	15.05	kN	Yes	10 Times	
Ref :		14.75	kN			
LCP :	2.0 %	14.46	kN	Yes	10 Times	
LEP :	25.0 %	11.07	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	10.33	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.45	kN	Min :	2.34	kN	Punch NO.;	16
SD :	2.10	%	Max :	2.59	kN	Punch NO.;	2
Mean Main Pressure :	14.90	kN	Min :	14.30	kN	Punch NO.;	47
SD :	2.00	%	Max :	15.51	kN	Punch NO.;	20
Filling Depth :	Increase ;	1	Times	Decrease ;	0	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.52	mm	Main Thickness ;	2.02	mm
Filling Depth :	7.51	mm	Current Cam :	Cam C	
Main Air pressure :	0.823	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	33	Min			
Lower Punch Remain Time (S2):	35	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.04	kN	Max Punch ;	49
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.17	kN	Max Punch ;	46
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	34

Tablet Data (N/A)

Total Counter :	150094	Tablets			
A.W.C Counter :	140891	Tablets			
HEP :	43 (0.0%)	Tablets	LEP :	125 (0.1%)	Tablets
GOOD :	140723 (99.9%)	Tablets			