

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	pb97604	Batch NO. :	VIM2500140
Print Interval :	50000 Tablets	Running Time :	03 Hour 33 Min 42 Sec
Total Counter :	650382	Total Running Time :	366 Hour 58 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	45	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.70	kN	No		
HEP :	25.0 %	18.94	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	15.46	kN	Yes	10 Times	
Ref :		15.16	kN			
LCP :	2.0 %	14.85	kN	Yes	10 Times	
LEP :	25.0 %	11.37	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	10.61	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.46	kN	Min :	2.39	kN	Punch NO.;	57
SD :	1.50	%	Max :	2.56	kN	Punch NO.;	22
Mean Main Pressure :	15.26	kN	Min :	14.58	kN	Punch NO.;	12
SD :	1.60	%	Max :	15.86	kN	Punch NO.;	20
Filling Depth :	Increase ;	4	Times	Decrease ;	13	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.44	mm	Main Thickness ;	1.94	mm
Filling Depth :	7.26	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.823	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	45	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.03	kN	Max Punch ;	24
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.17	kN	Max Punch ;	12
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	650382	Tablets			
A.W.C Counter :	640851	Tablets			
HEP :	43 (0.0%)	Tablets	LEP :	125 (0.0%)	Tablets
GOOD :	640683 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	pb97604	Batch NO. :	VIM2500140
Print Interval :	50000 Tablets	Running Time :	03 Hour 33 Min 42 Sec
Total Counter :	650382	Total Running Time :	366 Hour 58 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	59	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.02	kN	No		
HEP :	25.0 %	19.25	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	15.71	kN	Yes	10 Times	
Ref :		15.40	kN			
LCP :	2.0 %	15.09	kN	Yes	10 Times	
LEP :	25.0 %	11.55	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	10.78	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.38	kN	Min :	2.25	kN	Punch NO.;	32
SD :	2.10	%	Max :	2.49	kN	Punch NO.;	20
Mean Main Pressure :	15.51	kN	Min :	14.79	kN	Punch NO.;	14
SD :	2.10	%	Max :	16.37	kN	Punch NO.;	30
Filling Depth :	Increase ;	1	Times	Decrease ;	12	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.52	mm	Main Thickness ;	2.02	mm
Filling Depth :	7.46	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.823	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	45	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.05	kN	Max Punch ;	55
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.17	kN	Max Punch ;	12
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	650382	Tablets			
A.W.C Counter :	640851	Tablets			
HEP :	43 (0.0%)	Tablets	LEP :	125 (0.0%)	Tablets
GOOD :	640683 (100.0%)	Tablets			