

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	pl98382	Batch NO. :	VIM2500140
Print Interval :	50000 Tablets	Running Time :	04 Hour 04 Min 32 Sec
Total Counter :	750446	Total Running Time :	367 Hour 29 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	45	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.70	kN	No		
HEP :	25.0 %	18.94	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	15.46	kN	Yes	10 Times	
Ref :		15.16	kN			
LCP :	2.0 %	14.85	kN	Yes	10 Times	
LEP :	25.0 %	11.37	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	10.61	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.37	kN	Min :	2.19	kN	Punch NO.;	26
SD :	3.10	%	Max :	2.53	kN	Punch NO.;	9
Mean Main Pressure :	14.92	kN	Min :	12.94	kN	Punch NO.;	7
SD :	4.00	%	Max :	15.93	kN	Punch NO.;	20
Filling Depth :	Increase ; 4	Times	Decrease ;	13	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.44	mm	Main Thickness ;	1.94	mm
Filling Depth :	7.26	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.802	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	36	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.10	kN	Max Punch ;	7
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.14	kN	Max Punch ;	52
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	3

Tablet Data (N/A)

Total Counter :	750446	Tablets			
A.W.C Counter :	740700	Tablets			
HEP :	43 (0.0%)	Tablets	LEP :	125 (0.0%)	Tablets
GOOD :	740532 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	pl98382	Batch NO. :	VIM2500140
Print Interval :	50000 Tablets	Running Time :	04 Hour 04 Min 32 Sec
Total Counter :	750446	Total Running Time :	367 Hour 29 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	59	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.02	kN	No		
HEP :	25.0 %	19.25	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.71	kN	Yes 10	Times	
Ref :		15.40	kN			
LCP :	2.0 %	15.09	kN	Yes 10	Times	
LEP :	25.0 %	11.55	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.78	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.24	kN	Min :	2.17	kN	Punch NO.;	30
SD :	1.80	%	Max :	2.34	kN	Punch NO.;	53
Mean Main Pressure :	15.20	kN	Min :	14.59	kN	Punch NO.;	14
SD :	1.80	%	Max :	15.85	kN	Punch NO.;	30
Filling Depth :	Increase ;	1	Times	Decrease ;	12	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.52	mm	Main Thickness ;	2.02	mm
Filling Depth :	7.46	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.802	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	36	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.10	kN	Max Punch ;	7
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.15	kN	Max Punch ;	12
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.10	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	750446	Tablets			
A.W.C Counter :	740700	Tablets			
HEP :	43 (0.0%)	Tablets	LEP :	125 (0.0%)	Tablets
GOOD :	740532 (100.0%)	Tablets			