

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	ka89411	Batch NO. :	VIM2500140
Print Interval :	50000 Tablets	Running Time :	04 Hour 09 Min 24 Sec
Total Counter :	763072	Total Running Time :	367 Hour 34 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	45	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.80	kN	No		
HEP :	25.0 %	19.04	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.54	kN	Yes 10	Times	
Ref :		15.23	kN			
LCP :	2.0 %	14.93	kN	Yes 10	Times	
LEP :	25.0 %	11.43	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.66	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.62	kN	Min :	2.58	kN	Punch NO.;	23
SD :	1.00	%	Max :	2.70	kN	Punch NO.;	27
Mean Main Pressure :	15.28	kN	Min :	14.68	kN	Punch NO.;	7
SD :	1.70	%	Max :	15.86	kN	Punch NO.;	58
Filling Depth :	Increase ; 4	Times	Decrease ;	14	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.44	mm	Main Thickness ;	1.94	mm
Filling Depth :	7.65	mm	Current Cam :	Cam C	
Main Air pressure :	0.805	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	33	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.07	kN	Max Punch ;	53
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.15	kN	Max Punch ;	12
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	763072	Tablets			
A.W.C Counter :	750924	Tablets			
HEP :	97 (0.0%)	Tablets	LEP :	129 (0.0%)	Tablets
GOOD :	750698 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	ka89411	Batch NO. :	VIM2500140
Print Interval :	50000 Tablets	Running Time :	04 Hour 09 Min 24 Sec
Total Counter :	763072	Total Running Time :	367 Hour 34 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	59	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.78	kN	No		
HEP :	25.0 %	19.02	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.52	kN	Yes 10	Times	
Ref :		15.22	kN			
LCP :	2.0 %	14.91	kN	Yes 10	Times	
LEP :	25.0 %	11.41	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.65	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.32	kN	Min :	2.25	kN	Punch NO.;	13
SD :	1.80	%	Max :	2.46	kN	Punch NO.;	46
Mean Main Pressure :	15.35	kN	Min :	14.81	kN	Punch NO.;	17
SD :	1.70	%	Max :	16.17	kN	Punch NO.;	30
Filling Depth :	Increase ;	1	Times	Decrease ;	13	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.52	mm	Main Thickness ;	2.02	mm
Filling Depth :	7.57	mm	Current Cam :	Cam C	
Main Air pressure :	0.805	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	33	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.07	kN	Max Punch ;	53
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.15	kN	Max Punch ;	20
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	763072	Tablets			
A.W.C Counter :	750989	Tablets			
HEP :	97 (0.0%)	Tablets	LEP :	129 (0.0%)	Tablets
GOOD :	750763 (100.0%)	Tablets			