

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	pb97604	Batch NO. :	VIM2500240
Print Interval :	50000 Tablets	Running Time :	00 Hour 43 Min 33 Sec
Total Counter :	100078	Total Running Time :	372 Hour 52 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	45	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.43	kN	No		
HEP :	25.0 %	18.68	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.25	kN	Yes 10	Times	
Ref :		14.95	kN			
LCP :	2.0 %	14.65	kN	Yes 10	Times	
LEP :	25.0 %	11.21	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.46	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.72	kN	Min :	2.64	kN	Punch NO.;	63
SD :	1.30	%	Max :	2.81	kN	Punch NO.;	9
Mean Main Pressure :	14.96	kN	Min :	14.30	kN	Punch NO.;	14
SD :	1.80	%	Max :	15.66	kN	Punch NO.;	20
Filling Depth :	Increase ; 14	Times	Decrease ; 29	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.46	mm	Main Thickness ;	1.96	mm
Filling Depth :	8.01	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.799	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.05	kN	Max Punch ;	26
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.17	kN	Max Punch ;	11
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	100078	Tablets			
A.W.C Counter :	90092	Tablets			
HEP :	0 (0%)	Tablets	LEP :	22 (0.0%)	Tablets
GOOD :	90070 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	pb97604	Batch NO. :	VIM2500240
Print Interval :	50000 Tablets	Running Time :	00 Hour 43 Min 33 Sec
Total Counter :	100078	Total Running Time :	372 Hour 52 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	59	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.53	kN	No		
HEP :	25.0 %	18.78	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.32	kN	Yes 10	Times	
Ref :		15.02	kN			
LCP :	2.0 %	14.72	kN	Yes 10	Times	
LEP :	25.0 %	11.27	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.51	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.57	kN	Min :	2.45	kN	Punch NO.;	58
SD :	2.20	%	Max :	2.75	kN	Punch NO.;	46
Mean Main Pressure :	15.03	kN	Min :	14.48	kN	Punch NO.;	17
SD :	2.10	%	Max :	15.86	kN	Punch NO.;	30
Filling Depth :	Increase ;	12	Times	Decrease ;	19	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.53	mm	Main Thickness ;	2.03	mm
Filling Depth :	7.89	mm	Current Cam :	Cam C	
Main Air pressure :	0.799	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.05	kN	Max Punch ;	26
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.17	kN	Max Punch ;	11
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	100078	Tablets			
A.W.C Counter :	90092	Tablets			
HEP :	0 (0%)	Tablets	LEP :	22 (0.0%)	Tablets
GOOD :	90070 (100.0%)	Tablets			