

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	pn98247	Batch NO. :	MRM2500285
Print Interval :	50000 Tablets	Running Time :	01 Hour 03 Min 17 Sec
Total Counter :	100012	Total Running Time :	381 Hour 59 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	60	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2647059	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.79	kN	No		
HEP :	25.0 %	19.03	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.53	kN	Yes 10	Times	
Ref :		15.22	kN			
LCP :	2.0 %	14.92	kN	Yes 10	Times	
LEP :	25.0 %	11.42	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.66	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	8.40	kN	Min :	8.23	kN	Punch NO.;	24
SD :	1.00	%	Max :	8.63	kN	Punch NO.;	9
Mean Main Pressure :	15.52	kN	Min :	14.78	kN	Punch NO.;	20
SD :	2.00	%	Max :	16.34	kN	Punch NO.;	9
Filling Depth :	Increase ; 31	Times	Decrease ; 37	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.70	mm	Pre Thickness ;	4.20	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	6.05	mm	Main Thickness ;	3.55	mm
Filling Depth :	8.54	mm	Current Cam :	Cam C	
Main Air pressure :	0.804	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	69	Min			
Lower Punch Remain Time (S2):	51	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.37	kN	Max Punch ;	24
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.17	kN	Max Punch ;	4
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.12	kN	Max Punch ;	47

Tablet Data (N/A)

Total Counter :	100012	Tablets			
A.W.C Counter :	52718	Tablets			
HEP :	8 (0.0%)	Tablets	LEP :	6 (0.0%)	Tablets
GOOD :	52704 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	pn98247	Batch NO. :	MRM2500285
Print Interval :	50000 Tablets	Running Time :	01 Hour 03 Min 17 Sec
Total Counter :	100012	Total Running Time :	381 Hour 59 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	60	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2647059	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.12	kN	No		
HEP :	25.0 %	18.39	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.00	kN	Yes 10	Times	
Ref :		14.71	kN			
LCP :	2.0 %	14.42	kN	Yes 10	Times	
LEP :	25.0 %	11.03	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.30	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	8.59	kN	Min :	8.31	kN	Punch NO.;	33
SD :	1.50	%	Max :	8.87	kN	Punch NO.;	16
Mean Main Pressure :	14.82	kN	Min :	14.08	kN	Punch NO.;	33
SD :	2.80	%	Max :	15.79	kN	Punch NO.;	16
Filling Depth :	Increase ;	25	Times	Decrease ;	12	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.70	mm	Pre Thickness ;	4.20	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	6.15	mm	Main Thickness ;	3.65	mm
Filling Depth :	8.74	mm	Current Cam :	Cam C	
Main Air pressure :	0.804	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	69	Min			
Lower Punch Remain Time (S2):	51	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.39	kN	Max Punch ;	24
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.17	kN	Max Punch ;	4
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.12	kN	Max Punch ;	47

Tablet Data (N/A)

Total Counter :	100012	Tablets			
A.W.C Counter :	52718	Tablets			
HEP :	8 (0.0%)	Tablets	LEP :	6 (0.0%)	Tablets
GOOD :	52704 (100.0%)	Tablets			