

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	rp98927	Batch NO. :	MRM2500285
Print Interval :	50000 Tablets	Running Time :	00 Hour 43 Min 23 Sec
Total Counter :	2350694	Total Running Time :	405 Hour 41 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	119	%	Manual ;	60	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2647059	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.54	kN	No		
HEP :	25.0 %	18.79	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.33	kN	Yes 10	Times	
Ref :		15.03	kN			
LCP :	2.0 %	14.73	kN	Yes 10	Times	
LEP :	25.0 %	11.27	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.52	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	8.16	kN	Min :	8.05	kN	Punch NO.;	1
SD :	0.50	%	Max :	8.26	kN	Punch NO.;	48
Mean Main Pressure :	14.98	kN	Min :	14.33	kN	Punch NO.;	10
SD :	1.90	%	Max :	15.61	kN	Punch NO.;	40
Filling Depth :	Increase ;	525	Times	Decrease ;	397	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.85	mm	Pre Thickness ;	4.35	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.95	mm	Main Thickness ;	3.45	mm
Filling Depth :	8.88	mm	Current Cam :	Cam C	
Main Air pressure :	0.813	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	33	Min			
Lower Punch Remain Time (S2):	35	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.35	kN		
	Max ;	0.40	kN	Max Punch ;	24
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.15	kN	Max Punch ;	49
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.07	kN	Max Punch ;	45

Tablet Data (N/A)

Total Counter :	2350694	Tablets			
A.W.C Counter :	2295024	Tablets			
HEP :	154 (0.0%)	Tablets	LEP :	285 (0.0%)	Tablets
GOOD :	2294585 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	rp98927	Batch NO. :	MRM2500285
Print Interval :	50000 Tablets	Running Time :	00 Hour 43 Min 23 Sec
Total Counter :	2350694	Total Running Time :	405 Hour 41 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	119	%	Manual ;	60	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2647059	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.55	kN	No		
HEP :	25.0 %	20.72	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.91	kN	Yes 10	Times	
Ref :		16.58	kN			
LCP :	2.0 %	16.25	kN	Yes 10	Times	
LEP :	25.0 %	12.43	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.60	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	7.94	kN	Min :	7.86	kN	Punch NO.;	27
SD :	0.50	%	Max :	8.03	kN	Punch NO.;	14
Mean Main Pressure :	16.61	kN	Min :	15.97	kN	Punch NO.;	11
SD :	1.90	%	Max :	17.23	kN	Punch NO.;	16
Filling Depth :	Increase ;	169	Times	Decrease ;	181	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.95	mm	Pre Thickness ;	4.45	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	6.05	mm	Main Thickness ;	3.55	mm
Filling Depth :	9.09	mm	Current Cam :	Cam C	
Main Air pressure :	0.813	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	33	Min			
Lower Punch Remain Time (S2):	35	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.35	kN		
	Max ;	0.40	kN	Max Punch ;	19
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.15	kN	Max Punch ;	49
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.07	kN	Max Punch ;	45

Tablet Data (N/A)

Total Counter :	2350694	Tablets			
A.W.C Counter :	2295024	Tablets			
HEP :	154 (0.0%)	Tablets	LEP :	285 (0.0%)	Tablets
GOOD :	2294585 (100.0%)	Tablets			