

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STM7B00
User ID :	pb97604	Batch NO. :	MRM2500185
Print Interval :	50000 Tablets	Running Time :	02 Hour 38 Min 14 Sec
Total Counter :	250052	Total Running Time :	411 Hour 14 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	119	%	Manual ;	60	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2647059	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.08	kN	No		
HEP :	25.0 %	19.30	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.75	kN	Yes 10	Times	
Ref :		15.44	kN			
LCP :	2.0 %	15.13	kN	Yes 10	Times	
LEP :	25.0 %	11.58	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.81	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	8.12	kN	Min :	8.01	kN	Punch NO.;	50
SD :	0.50	%	Max :	8.20	kN	Punch NO.;	35
Mean Main Pressure :	15.43	kN	Min :	14.65	kN	Punch NO.;	50
SD :	1.90	%	Max :	16.03	kN	Punch NO.;	35
Filling Depth :	Increase ; 11	Times	Decrease ; 12	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.90	mm	Pre Thickness ;	4.40	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.95	mm	Main Thickness ;	3.45	mm
Filling Depth :	9.29	mm	Current Cam :	Cam C	
Main Air pressure :	0.795	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	30	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.38	kN		
	Max ;	0.44	kN	Max Punch ;	23
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	31
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	38

Tablet Data (N/A)

Total Counter :	250052	Tablets			
A.W.C Counter :	246217	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	246217 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	pb97604	Batch NO. :	MRM2500185
Print Interval :	50000 Tablets	Running Time :	02 Hour 38 Min 14 Sec
Total Counter :	250052	Total Running Time :	411 Hour 14 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	119	%	Manual ;	60	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2647059	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	22.94	kN	No		
HEP :	25.0 %	22.05	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	18.00	kN	Yes 10	Times	
Ref :		17.64	kN			
LCP :	2.0 %	17.29	kN	Yes 10	Times	
LEP :	25.0 %	13.23	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	12.35	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	8.19	kN	Min :	8.06	kN	Punch NO.;	36
SD :	0.80	%	Max :	8.32	kN	Punch NO.;	32
Mean Main Pressure :	17.88	kN	Min :	17.04	kN	Punch NO.;	3
SD :	2.30	%	Max :	18.66	kN	Punch NO.;	32
Filling Depth :	Increase ;	3	Times	Decrease ;	11	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.99	mm	Pre Thickness ;	4.49	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	6.00	mm	Main Thickness ;	3.50	mm
Filling Depth :	9.54	mm	Current Cam :	Cam C	
Main Air pressure :	0.795	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	30	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.38	kN		
	Max ;	0.43	kN	Max Punch ;	51
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	31
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	38

Tablet Data (N/A)

Total Counter :	250052	Tablets			
A.W.C Counter :	246270	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	246270 (100.0%)	Tablets			