

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STM7B00
User ID :	ka98463	Batch NO. :	MRM2500185
Print Interval :	50000 Tablets	Running Time :	09 Hour 21 Min 00 Sec
Total Counter :	1000218	Total Running Time :	417 Hour 57 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	147	%	Manual ;	60	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2647059	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.01	kN	No		
HEP :	25.0 %	20.20	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.48	kN	Yes 15	Times	
Ref :		16.16	kN			
LCP :	2.0 %	15.84	kN	Yes 15	Times	
LEP :	25.0 %	12.12	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.31	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	6.20	kN	Min :	6.11	kN	Punch NO.;	23
		0.80	%	Max :	6.46	kN	Punch NO.;	5
Mean Main Pressure :		16.58	kN	Min :	15.66	kN	Punch NO.;	50
	SD :	2.50	%	Max :	18.47	kN	Punch NO.;	5
Filling Depth :	Increase ;	131	Times	Decrease ;	157	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.89	mm	Pre Thickness ;	4.39	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.95	mm	Main Thickness ;	3.45	mm
Filling Depth :	9.32	mm	Current Cam :	Cam C	
Main Air pressure :	0.798	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	38	Min			
Lower Punch Remain Time (S2):	40	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.33	kN		
	Max ;	0.37	kN	Max Punch ;	24
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	53
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.13	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	1000218	Tablets			
A.W.C Counter :	994400	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	141 (0.0%)	Tablets
GOOD :	994249 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	ka98463	Batch NO. :	MRM2500185
Print Interval :	50000 Tablets	Running Time :	09 Hour 21 Min 00 Sec
Total Counter :	1000218	Total Running Time :	417 Hour 57 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	119	%	Manual ;	60	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2647059	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.51	kN	No		
HEP :	25.0 %	20.68	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.88	kN	Yes 15	Times	
Ref :		16.55	kN			
LCP :	2.0 %	16.22	kN	Yes 15	Times	
LEP :	25.0 %	12.41	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.58	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	6.45	kN	Min :	6.34	kN	Punch NO.;	7
SD :	0.70	%	Max :	6.59	kN	Punch NO.;	5
Mean Main Pressure :	16.76	kN	Min :	15.98	kN	Punch NO.;	7
SD :	2.30	%	Max :	17.78	kN	Punch NO.;	5
Filling Depth :	Increase ;	41	Times	Decrease ;	57	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	21	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.99	mm	Pre Thickness ;	4.49	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	6.00	mm	Main Thickness ;	3.50	mm
Filling Depth :	9.11	mm	Current Cam :	Cam C	
Main Air pressure :	0.798	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	38	Min			
Lower Punch Remain Time (S2):	40	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.33	kN		
	Max ;	0.37	kN	Max Punch ;	52
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	53
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.13	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	1000218	Tablets			
A.W.C Counter :	994400	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	141 (0.0%)	Tablets
GOOD :	994249 (100.0%)	Tablets			