

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	pb97604	Batch NO. :	MRM2500385
Print Interval :	50000 Tablets	Running Time :	00 Hour 52 Min 32 Sec
Total Counter :	100032	Total Running Time :	433 Hour 16 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	160	%	Manual ;	76	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2647059	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.92	kN	No		
HEP :	23.0 %	18.84	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.63	kN	Yes 15	Times	
Ref :		15.32	kN			
LCP :	2.0 %	15.01	kN	Yes 15	Times	
LEP :	23.0 %	11.80	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.72	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	5.88	kN	Min :	5.74	kN	Punch NO.;	27
SD :	0.80	%	Max :	6.04	kN	Punch NO.;	9
Mean Main Pressure :	15.60	kN	Min :	14.69	kN	Punch NO.;	4
SD :	2.30	%	Max :	16.95	kN	Punch NO.;	9
Filling Depth :	Increase ;	860	Times	Decrease ;	925	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	29	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.89	mm	Pre Thickness ;	4.39	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.95	mm	Main Thickness ;	3.45	mm
Filling Depth :	8.56	mm	Current Cam :	Cam C	
Main Air pressure :	0.794	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	39	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.31	kN		
	Max ;	0.36	kN	Max Punch ;	50
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.15	kN	Max Punch ;	49
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.07	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	100032	Tablets			
A.W.C Counter :	98417	Tablets			
HEP :	517 (0.5%)	Tablets	LEP :	76 (0.1%)	Tablets
GOOD :	97824 (99.4%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	pb97604	Batch NO. :	MRM2500385
Print Interval :	50000 Tablets	Running Time :	00 Hour 52 Min 32 Sec
Total Counter :	100032	Total Running Time :	433 Hour 16 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	166	%	Manual ;	60	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2647059	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.97	kN	No		
HEP :	23.0 %	19.85	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.46	kN	Yes 15	Times	
Ref :		16.13	kN			
LCP :	2.0 %	15.81	kN	Yes 15	Times	
LEP :	23.0 %	12.42	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.29	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	6.37	kN	Min :	6.24	kN	Punch NO.;	32
SD :	0.80	%	Max :	6.49	kN	Punch NO.;	4
Mean Main Pressure :	16.13	kN	Min :	15.16	kN	Punch NO.;	23
SD :	2.70	%	Max :	17.23	kN	Punch NO.;	49
Filling Depth :	Increase ;	507	Times	Decrease ;	503	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.99	mm	Pre Thickness ;	4.49	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	6.00	mm	Main Thickness ;	3.50	mm
Filling Depth :	8.75	mm	Current Cam :	Cam C	
Main Air pressure :	0.794	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	39	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.31	kN		
	Max ;	0.37	kN	Max Punch ;	1
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.15	kN	Max Punch ;	49
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.07	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	100032	Tablets			
A.W.C Counter :	98417	Tablets			
HEP :	517 (0.5%)	Tablets	LEP :	76 (0.1%)	Tablets
GOOD :	97824 (99.4%)	Tablets			