

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	pb97604	Batch NO. :	MRM2500385
Print Interval :	50000 Tablets	Running Time :	01 Hour 18 Min 49 Sec
Total Counter :	150040	Total Running Time :	433 Hour 42 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	160	%	Manual ;	76	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2647059	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.92	kN	No		
HEP :	23.0 %	18.84	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.63	kN	Yes 15	Times	
Ref :		15.32	kN			
LCP :	2.0 %	15.01	kN	Yes 15	Times	
LEP :	23.0 %	11.80	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.72	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	5.82	kN	Min :	5.74	kN	Punch NO.;	19
SD :	0.80	%	Max :	6.06	kN	Punch NO.;	5
Mean Main Pressure :	15.26	kN	Min :	14.55	kN	Punch NO.;	15
SD :	2.70	%	Max :	17.15	kN	Punch NO.;	5
Filling Depth :	Increase ;	860	Times	Decrease ;	926	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	29	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.89	mm	Pre Thickness ;	4.39	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.95	mm	Main Thickness ;	3.45	mm
Filling Depth :	8.53	mm	Current Cam :	Cam C	
Main Air pressure :	0.802	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	70	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.31	kN		
	Max ;	0.36	kN	Max Punch ;	53
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.15	kN	Max Punch ;	33
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	38

Tablet Data (N/A)

Total Counter :	150040	Tablets			
A.W.C Counter :	148396	Tablets			
HEP :	520 (0.4%)	Tablets	LEP :	76 (0.1%)	Tablets
GOOD :	147800 (99.6%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	pb97604	Batch NO. :	MRM2500385
Print Interval :	50000 Tablets	Running Time :	01 Hour 18 Min 49 Sec
Total Counter :	150040	Total Running Time :	433 Hour 42 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	166	%	Manual ;	60	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2647059	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.97	kN	No		
HEP :	23.0 %	19.85	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.46	kN	Yes 15	Times	
Ref :		16.13	kN			
LCP :	2.0 %	15.81	kN	Yes 15	Times	
LEP :	23.0 %	12.42	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.29	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	6.37	kN	Min :	6.27	kN	Punch NO.;	25
SD :	0.90	%	Max :	6.55	kN	Punch NO.;	9
Mean Main Pressure :	16.16	kN	Min :	15.37	kN	Punch NO.;	31
SD :	2.70	%	Max :	17.42	kN	Punch NO.;	9
Filling Depth :	Increase ;	513	Times	Decrease ;	508	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.99	mm	Pre Thickness ;	4.49	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	6.00	mm	Main Thickness ;	3.50	mm
Filling Depth :	8.78	mm	Current Cam :	Cam C	
Main Air pressure :	0.802	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	70	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.30	kN		
	Max ;	0.36	kN	Max Punch ;	52
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.15	kN	Max Punch ;	33
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	38

Tablet Data (N/A)

Total Counter :	150040	Tablets			
A.W.C Counter :	148449	Tablets			
HEP :	520 (0.4%)	Tablets	LEP :	76 (0.1%)	Tablets
GOOD :	147853 (99.6%)	Tablets			