

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	pb97604	Batch NO. :	MRM2500385
Print Interval :	50000 Tablets	Running Time :	02 Hour 37 Min 40 Sec
Total Counter :	300056	Total Running Time :	435 Hour 1 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	160	%	Manual ;	76	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2647059	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.03	kN	No		
HEP :	23.0 %	18.95	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	15.71	kN	Yes	15 Times	
Ref :		15.40	kN			
LCP :	2.0 %	15.10	kN	Yes	15 Times	
LEP :	23.0 %	11.86	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	10.78	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	5.85	kN	Min :	5.73	kN	Punch NO.;	53
SD :	0.60	%	Max :	5.92	kN	Punch NO.;	30
Mean Main Pressure :	15.66	kN	Min :	14.75	kN	Punch NO.;	53
SD :	2.00	%	Max :	16.27	kN	Punch NO.;	39
Filling Depth :	Increase ;	862	Times	Decrease ;	928	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	29	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.89	mm	Pre Thickness ;	4.39	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.95	mm	Main Thickness ;	3.45	mm
Filling Depth :	8.59	mm	Current Cam :	Cam C	
Main Air pressure :	0.809	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	71	Min			
Lower Punch Remain Time (S2):	53	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.37	kN	Max Punch ;	1
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.18	kN	Max Punch ;	9
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	38

Tablet Data (N/A)

Total Counter :	300056	Tablets			
A.W.C Counter :	298439	Tablets			
HEP :	523 (0.2%)	Tablets	LEP :	76 (0.0%)	Tablets
GOOD :	297840 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	pb97604	Batch NO. :	MRM2500385
Print Interval :	50000 Tablets	Running Time :	02 Hour 37 Min 40 Sec
Total Counter :	300056	Total Running Time :	435 Hour 1 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	166	%	Manual ;	60	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2647059	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.94	kN	No		
HEP :	23.0 %	19.82	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.43	kN	Yes 15	Times	
Ref :		16.11	kN			
LCP :	2.0 %	15.79	kN	Yes 15	Times	
LEP :	23.0 %	12.41	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.28	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	6.37	kN	Min :	6.24	kN	Punch NO.;	50
SD :	1.30	%	Max :	6.81	kN	Punch NO.;	36
Mean Main Pressure :	16.30	kN	Min :	15.31	kN	Punch NO.;	4
SD :	4.70	%	Max :	20.44	kN	Punch NO.;	36
Filling Depth :	Increase ;	519	Times	Decrease ;	521	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.99	mm	Pre Thickness ;	4.49	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	6.00	mm	Main Thickness ;	3.50	mm
Filling Depth :	8.54	mm	Current Cam :	Cam C	
Main Air pressure :	0.809	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	71	Min			
Lower Punch Remain Time (S2):	53	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.36	kN	Max Punch ;	52
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.18	kN	Max Punch ;	9
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	38

Tablet Data (N/A)

Total Counter :	300056	Tablets			
A.W.C Counter :	298439	Tablets			
HEP :	523 (0.2%)	Tablets	LEP :	76 (0.0%)	Tablets
GOOD :	297840 (99.8%)	Tablets			