

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | METFORM 850<br>STMR7B00 |
| User ID :        | ka98463       | Batch NO. :          | MRM2500385              |
| Print Interval : | 50000 Tablets | Running Time :       | 16 Hour 12 Min 43 Sec   |
| Total Counter :  | 1850524       | Total Running Time : | 448 Hour 37 Min         |
| Station :        | Station 1     |                      |                         |

### Setting Value

|                                    |             |          |         |                    |              |           |
|------------------------------------|-------------|----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 160      | %       | Manual ;           | 76           | RPM       |
| Filling Cam :                      |             | Cam C    |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |             | 8.5-14mm |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |             | 2647059  | Tablets |                    |              |           |
| Air Pressure Low Limit :           |             | 0.000    | MPa     |                    |              |           |
| Oil Lubrication :                  |             |          |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 80       | Min     | Supply Time ;      | 0.3          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 60       | Min     | Supply Time ;      | 0.3          | Sec       |
| Powder Supply Time :               |             | 5.0      | Sec     |                    |              |           |
| Initial Reject Time :              |             | 2        | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 1.00     | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 1.00     | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 1.00     | kN      |                    |              |           |
|                                    |             |          |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 %      | 20.50    | kN      | No                 |              |           |
| HEP :                              | 23.0 %      | 19.40    | kN      | Yes 10             | Rotations 10 | Tablets   |
| HCP :                              | 2.0 %       | 16.09    | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 15.77    | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 15.46    | kN      | Yes 15             | Times        |           |
| LEP :                              | 23.0 %      | 12.14    | kN      | Yes 10             | Rotations 10 | Tablets   |
| LSP :                              | 30.0 %      | 11.04    | kN      | No                 |              |           |
| SD limit :                         | 35.0 %      |          |         | Yes                |              |           |
| Pre HSP                            |             | 30.00    | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |          |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | None        |          |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |      |            |    |
|----------------------|------------|-----|-------|------------|------|------------|----|
| Mean Pre Pressure :  | 5.88       | kN  | Min : | 5.81       | kN   | Punch NO.; | 15 |
| SD :                 | 0.60       | %   | Max : | 5.98       | kN   | Punch NO.; | 13 |
| Mean Main Pressure : | 15.79      | kN  | Min : | 14.79      | kN   | Punch NO.; | 15 |
| SD :                 | 2.20       | %   | Max : | 16.70      | kN   | Punch NO.; | 13 |
| Filling Depth :      | Increase ; | 964 | Times | Decrease ; | 1074 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 18      | RPM | Capacity :       | 114480   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 29       | RPM          |
| Pre Upper Punch Position ;    | 2.50    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 6.89    | mm  | Pre Thickness ;  | 4.39     | mm           |
| Main Upper Punch Position ;   | 2.50    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.95    | mm  | Main Thickness ; | 3.45     | mm           |
| Filling Depth :               | 8.50    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.755   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 62      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 24      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.35 | kN |             |    |
|                  | Max ;     | 0.39 | kN | Max Punch ; | 50 |
| Lower Punch :    | Average ; | 0.13 | kN |             |    |
|                  | Max ;     | 0.19 | kN | Max Punch ; | 12 |
| Ejection Force : | Average ; | 0.06 | kN |             |    |
|                  | Max ;     | 0.10 | kN | Max Punch ; | 11 |

### Tablet Data (N/A)

|                 |                  |         |       |            |         |
|-----------------|------------------|---------|-------|------------|---------|
| Total Counter : | 1850524          | Tablets |       |            |         |
| A.W.C Counter : | 1848074          | Tablets |       |            |         |
| HEP :           | 661 (0.0%)       | Tablets | LEP : | 129 (0.0%) | Tablets |
| GOOD :          | 1847284 (100.0%) | Tablets |       |            |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | METFORM 850<br>STMR7B00 |
| User ID :        | ka98463       | Batch NO. :          | MRM2500385              |
| Print Interval : | 50000 Tablets | Running Time :       | 16 Hour 12 Min 43 Sec   |
| Total Counter :  | 1850524       | Total Running Time : | 448 Hour 37 Min         |
| Station :        | Station 2     |                      |                         |

### Setting Value

|                                    |        |           |         |                    |              |           |
|------------------------------------|--------|-----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 166       | %       | Manual ;           | 60           | RPM       |
| Filling Cam :                      |        | Cam C     |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |        | 8.5-14mm  |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |        | 2647059   | Tablets |                    |              |           |
| Air Pressure Low Limit :           |        | 0.000     | MPa     |                    |              |           |
| Oil Lubrication :                  |        |           |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 80        | Min     | Supply Time ;      | 0.3          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 60        | Min     | Supply Time ;      | 0.3          | Sec       |
| Powder Supply Time :               |        | 5.0       | Sec     |                    |              |           |
| Initial Reject Time :              |        | 2         | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 1.00      | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 1.00      | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 1.00      | kN      |                    |              |           |
|                                    |        |           |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 % | 21.46     | kN      | No                 |              |           |
| HEP :                              | 23.0 % | 20.30     | kN      | Yes 10             | Rotations 10 | Tablets   |
| HCP :                              | 2.0 %  | 16.84     | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 16.51     | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 16.18     | kN      | Yes 15             | Times        |           |
| LEP :                              | 23.0 % | 12.71     | kN      | Yes 10             | Rotations 10 | Tablets   |
| LSP :                              | 30.0 % | 11.55     | kN      | No                 |              |           |
| SD limit :                         | 35.0 % |           |         | Yes                |              |           |
| Pre HSP                            |        | 30.00     | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | N      |           |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 6.53       | kN  | Min : | 6.46       | kN  | Punch NO.; | 4  |
| SD :                 | 0.70       | %   | Max : | 6.64       | kN  | Punch NO.; | 12 |
| Mean Main Pressure : | 16.47      | kN  | Min : | 15.70      | kN  | Punch NO.; | 26 |
| SD :                 | 2.40       | %   | Max : | 17.29      | kN  | Punch NO.; | 35 |
| Filling Depth :      | Increase ; | 624 | Times | Decrease ; | 645 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |                   |              |
|-------------------------------|---------|-----|------------------|-------------------|--------------|
| Disk Speed :                  | 18      | RPM | Capacity :       | 114480            | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 30                | RPM          |
| Pre Upper Punch Position ;    | 2.50    | mm  |                  |                   |              |
| Pre Lower Punch Position ;    | 6.99    | mm  | Pre Thickness ;  | 4.49              | mm           |
| Main Upper Punch Position ;   | 2.50    | mm  |                  |                   |              |
| Main Lower Punch Position ;   | 6.00    | mm  | Main Thickness ; | 3.50              | mm           |
| Filling Depth :               | 8.79    | mm  | Current Cam :    | Cam C<br>8.5-14mm |              |
| Main Air pressure :           | 0.755   | MPa |                  |                   |              |
| Oil Lubrication status :      |         |     |                  |                   |              |
| Upper Punch Remain Time (S1): | 62      | Min |                  |                   |              |
| Lower Punch Remain Time (S2): | 24      | Min |                  |                   |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |                   |              |
| Powder Status :               | Disable |     | Dust Collector : | Off               |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off               |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.35 | kN |             |    |
|                  | Max ;     | 0.39 | kN | Max Punch ; | 24 |
| Lower Punch :    | Average ; | 0.13 | kN |             |    |
|                  | Max ;     | 0.19 | kN | Max Punch ; | 12 |
| Ejection Force : | Average ; | 0.06 | kN |             |    |
|                  | Max ;     | 0.10 | kN | Max Punch ; | 11 |

### Tablet Data (N/A)

|                 |                     |         |       |            |         |
|-----------------|---------------------|---------|-------|------------|---------|
| Total Counter : | 1850524             | Tablets |       |            |         |
| A.W.C Counter : | 1848074             | Tablets |       |            |         |
| HEP :           | 661 (0.0%)          | Tablets | LEP : | 129 (0.0%) | Tablets |
| GOOD :          | 1847284<br>(100.0%) | Tablets |       |            |         |