

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	AMIOD 200MG STAI3A00
User ID :	rp98927	Batch NO. :	AIM2500120
Print Interval :	50000 Tablets	Running Time :	00 Hour 31 Min 48 Sec
Total Counter :	50018	Total Running Time :	478 Hour 40 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	84	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	22.11	kN	No		
HEP :	25.0 %	21.26	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	17.35	kN	Yes 15	Times	
Ref :		17.01	kN			
LCP :	2.0 %	16.67	kN	Yes 15	Times	
LEP :	25.0 %	12.76	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.91	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.36	kN	Min :	1.35	kN	Punch NO.;	14
SD :	0.40	%	Max :	1.38	kN	Punch NO.;	53
Mean Main Pressure :	16.78	kN	Min :	15.36	kN	Punch NO.;	45
SD :	4.00	%	Max :	18.37	kN	Punch NO.;	33
Filling Depth :	Increase ; 40	Times	Decrease ; 35	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.10	mm	Pre Thickness ;	4.11	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.00	mm	Main Thickness ;	1.01	mm
Filling Depth :	5.54	mm	Current Cam :	Cam B	
Main Air pressure :	0.759	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	50	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.38	kN		
	Max ;	0.48	kN	Max Punch ;	25
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	23
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	29

Tablet Data (N/A)

Total Counter :	50018	Tablets			
A.W.C Counter :	43525	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	43525 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	AMIOD 200MG STAI3A00
User ID :	rp98927	Batch NO. :	AIM2500120
Print Interval :	50000 Tablets	Running Time :	00 Hour 31 Min 48 Sec
Total Counter :	50018	Total Running Time :	478 Hour 40 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.74	kN	No		
HEP :	25.0 %	20.91	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	17.06	kN	Yes 15	Times	
Ref :		16.72	kN			
LCP :	2.0 %	16.39	kN	Yes 15	Times	
LEP :	25.0 %	12.54	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.71	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.10	kN	Min :	1.08	kN	Punch NO.;	52
SD :	0.70	%	Max :	1.13	kN	Punch NO.;	48
Mean Main Pressure :	16.75	kN	Min :	15.70	kN	Punch NO.;	22
SD :	3.40	%	Max :	18.00	kN	Punch NO.;	48
Filling Depth :	Increase ; 16	Times	Decrease ; 20	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.08	mm	Main Thickness ;	1.09	mm
Filling Depth :	5.49	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.759	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	50	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.38	kN		
	Max ;	0.48	kN	Max Punch ;	1
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	23
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	29

Tablet Data (N/A)

Total Counter :	50018	Tablets			
A.W.C Counter :	43578	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	43578 (100.0%)	Tablets			