

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	AMIOD 200MG STAI3A00
User ID :	pb97604	Batch NO. :	AIM2500120
Print Interval :	50000 Tablets	Running Time :	03 Hour 10 Min 00 Sec
Total Counter :	350148	Total Running Time :	481 Hour 19 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.15	kN	No		
HEP :	20.0 %	19.53	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	16.60	kN	Yes	15 Times	
Ref :		16.27	kN			
LCP :	2.0 %	15.95	kN	Yes	15 Times	
LEP :	20.0 %	13.02	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	11.39	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.58	kN	Min :	3.25	kN	Punch NO.;	52
SD :	4.90	%	Max :	3.97	kN	Punch NO.;	37
Mean Main Pressure :	16.37	kN	Min :	15.05	kN	Punch NO.;	15
SD :	3.10	%	Max :	17.42	kN	Punch NO.;	26
Filling Depth :	Increase ;	195	Times	Decrease ;	182	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.50	mm	Pre Thickness ;	1.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.95	mm	Main Thickness ;	0.96	mm
Filling Depth :	5.99	mm	Current Cam :	Cam B	
Main Air pressure :	0.762	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	56	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.25	kN		
	Max ;	0.34	kN	Max Punch ;	53
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	24
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	350148	Tablets			
A.W.C Counter :	338028	Tablets			
HEP :	35 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	337992 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	AMIOD 200MG STAI3A00
User ID :	pb97604	Batch NO. :	AIM2500120
Print Interval :	50000 Tablets	Running Time :	03 Hour 10 Min 00 Sec
Total Counter :	350148	Total Running Time :	481 Hour 19 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	111	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.60	kN	No		
HEP :	20.0 %	19.02	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.16	kN	Yes 15	Times	
Ref :		15.85	kN			
LCP :	2.0 %	15.53	kN	Yes 15	Times	
LEP :	20.0 %	12.68	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.09	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.91	kN	Min :	1.74	kN	Punch NO.;	24
SD :	3.30	%	Max :	2.02	kN	Punch NO.;	19
Mean Main Pressure :	15.98	kN	Min :	14.53	kN	Punch NO.;	45
SD :	3.10	%	Max :	17.19	kN	Punch NO.;	14
Filling Depth :	Increase ;	118	Times	Decrease ;	96	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.05	mm	Main Thickness ;	1.06	mm
Filling Depth :	5.97	mm	Current Cam :	Cam B	
Main Air pressure :	0.762	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	56	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.26	kN		
	Max ;	0.34	kN	Max Punch ;	1
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	24
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	350148	Tablets			
A.W.C Counter :	338081	Tablets			
HEP :	35 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	338045 (100.0%)	Tablets			