

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	AMIOD 200MG STAI3A00
User ID :	ms88737	Batch NO. :	AIM2500120
Print Interval :	50000 Tablets	Running Time :	10 Hour 22 Min 56 Sec
Total Counter :	1150364	Total Running Time :	488 Hour 32 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	124	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.86	kN	No		
HEP :	20.0 %	20.18	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	17.15	kN	Yes 15	Times	
Ref :		16.81	kN			
LCP :	2.0 %	16.48	kN	Yes 15	Times	
LEP :	20.0 %	13.45	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.77	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.75	kN	Min :	3.14	kN	Punch NO.;	11
SD :	7.00	%	Max :	4.47	kN	Punch NO.;	28
Mean Main Pressure :	17.01	kN	Min :	15.54	kN	Punch NO.;	7
SD :	3.90	%	Max :	18.60	kN	Punch NO.;	38
Filling Depth :	Increase ;	576	Times	Decrease ;	581	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	21	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.50	mm	Pre Thickness ;	1.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.95	mm	Main Thickness ;	0.96	mm
Filling Depth :	6.40	mm	Current Cam :	Cam B	
Main Air pressure :	0.810	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	33	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.28	kN		
	Max ;	0.38	kN	Max Punch ;	1
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	24
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	1

Tablet Data (N/A)

Total Counter :	1150364	Tablets			
A.W.C Counter :	1128687	Tablets			
HEP :	200 (0.0%)	Tablets	LEP :	148 (0.0%)	Tablets
GOOD :	1128339 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	AMIOD 200MG STAI3A00
User ID :	ms88737	Batch NO. :	AIM2500120
Print Interval :	50000 Tablets	Running Time :	10 Hour 22 Min 56 Sec
Total Counter :	1150364	Total Running Time :	488 Hour 32 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	99	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.69	kN	No		
HEP :	20.0 %	20.03	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	17.02	kN	Yes	15 Times	
Ref :		16.69	kN			
LCP :	2.0 %	16.35	kN	Yes	15 Times	
LEP :	20.0 %	13.35	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	11.68	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.98	kN	Min :	1.86	kN	Punch NO.;	53
SD :	3.20	%	Max :	2.15	kN	Punch NO.;	39
Mean Main Pressure :	16.92	kN	Min :	16.01	kN	Punch NO.;	9
SD :	2.80	%	Max :	18.15	kN	Punch NO.;	52
Filling Depth :	Increase ;	358	Times	Decrease ;	283	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	17	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.02	mm	Main Thickness ;	1.03	mm
Filling Depth :	6.56	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.810	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	33	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.28	kN		
	Max ;	0.38	kN	Max Punch ;	1
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	43
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.05	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	1150364	Tablets			
A.W.C Counter :	1128687	Tablets			
HEP :	200 (0.0%)	Tablets	LEP :	148 (0.0%)	Tablets
GOOD :	1128339 (100.0%)	Tablets			