

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO800mg STV11C00
User ID :	pb97604	Batch NO. :	VIM2500180
Print Interval :	50000 Tablets	Running Time :	04 Hour 12 Min 40 Sec
Total Counter :	500204	Total Running Time :	495 Hour 38 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	112	%	Manual ;	35	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.34	kN	No		
HEP :	25.0 %	24.37	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	19.89	kN	Yes 15	Times	
Ref :		19.50	kN			
LCP :	2.0 %	19.11	kN	Yes 15	Times	
LEP :	25.0 %	14.62	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	13.65	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.29	kN	Min :	2.16	kN	Punch NO.;	50
SD :	2.40	%	Max :	2.42	kN	Punch NO.;	43
Mean Main Pressure :	19.80	kN	Min :	19.21	kN	Punch NO.;	41
SD :	1.30	%	Max :	20.50	kN	Punch NO.;	27
Filling Depth :	Increase ; 3	Times	Decrease ;	63	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.40	mm	Pre Thickness ;	4.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.70	mm	Main Thickness ;	2.71	mm
Filling Depth :	9.48	mm	Current Cam :	Cam C	
Main Air pressure :	0.804	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	27	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.34	kN		
	Max ;	0.47	kN	Max Punch ;	51
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	20
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	27

Tablet Data (N/A)

Total Counter :	500204	Tablets			
A.W.C Counter :	489888	Tablets			
HEP :	28 (0.0%)	Tablets	LEP :	148 (0.0%)	Tablets
GOOD :	489712 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO800mg STV11C00
User ID :	pb97604	Batch NO. :	VIM2500180
Print Interval :	50000 Tablets	Running Time :	04 Hour 12 Min 40 Sec
Total Counter :	500204	Total Running Time :	495 Hour 38 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	110	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.25	kN	No		
HEP :	25.0 %	24.28	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	19.82	kN	Yes 15	Times	
Ref :		19.43	kN			
LCP :	2.0 %	19.04	kN	Yes 15	Times	
LEP :	25.0 %	14.57	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	13.60	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.75	kN	Min :	2.66	kN	Punch NO.;	50
SD :	1.80	%	Max :	2.87	kN	Punch NO.;	14
Mean Main Pressure :	19.60	kN	Min :	18.97	kN	Punch NO.;	18
SD :	1.80	%	Max :	20.70	kN	Punch NO.;	27
Filling Depth :	Increase ;	5	Times	Decrease ;	13	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.40	mm	Pre Thickness ;	4.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.78	mm	Main Thickness ;	2.79	mm
Filling Depth :	9.85	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.804	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	27	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.34	kN		
	Max ;	0.47	kN	Max Punch ;	25
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	20
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	27

Tablet Data (N/A)

Total Counter :	500204	Tablets			
A.W.C Counter :	489888	Tablets			
HEP :	28 (0.0%)	Tablets	LEP :	148 (0.0%)	Tablets
GOOD :	489712 (100.0%)	Tablets			