

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO800mg STV11C00
User ID :	vg96371	Batch NO. :	VIM2500280
Print Interval :	50000 Tablets	Running Time :	00 Hour 31 Min 48 Sec
Total Counter :	50010	Total Running Time :	498 Hour 17 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	84	%	Manual ;	35	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		750000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.22	kN	No		
HEP :	25.0 %	24.25	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	19.79	kN	Yes	15	Times
Ref :		19.40	kN			
LCP :	2.0 %	19.01	kN	Yes	15	Times
LEP :	25.0 %	14.55	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	13.58	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.33	kN	Min :	2.19	kN	Punch NO.;	12
		2.70	%	Max :	2.45	kN	Punch NO.;	43
Mean Main Pressure :		19.43	kN	Min :	18.74	kN	Punch NO.;	28
	SD :	1.50	%	Max :	20.13	kN	Punch NO.;	1
Filling Depth :	Increase ;	5	Times	Decrease ;	64	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.40	mm	Pre Thickness ;	4.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.70	mm	Main Thickness ;	2.71	mm
Filling Depth :	10.45	mm	Current Cam :	Cam C	
Main Air pressure :	0.784	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	33	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.41	kN		
	Max ;	0.54	kN	Max Punch ;	1
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	20
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	27

Tablet Data (N/A)

Total Counter :	50010	Tablets			
A.W.C Counter :	45673	Tablets			
HEP :	38 (0.1%)	Tablets	LEP :	34 (0.1%)	Tablets
GOOD :	45601 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO800mg STV11C00
User ID :	vg96371	Batch NO. :	VIM2500280
Print Interval :	50000 Tablets	Running Time :	00 Hour 31 Min 48 Sec
Total Counter :	50010	Total Running Time :	498 Hour 17 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	85	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		750000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.13	kN	No		
HEP :	25.0 %	24.16	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	19.71	kN	Yes 15	Times	
Ref :		19.33	kN			
LCP :	2.0 %	18.94	kN	Yes 15	Times	
LEP :	25.0 %	14.50	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	13.53	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.84	kN	Min :	2.72	kN	Punch NO.;	2
SD :	2.30	%	Max :	3.00	kN	Punch NO.;	14
Mean Main Pressure :	19.38	kN	Min :	18.63	kN	Punch NO.;	18
SD :	1.80	%	Max :	20.18	kN	Punch NO.;	27
Filling Depth :	Increase ; 6	Times	Decrease ;	14	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.40	mm	Pre Thickness ;	4.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.78	mm	Main Thickness ;	2.79	mm
Filling Depth :	10.35	mm	Current Cam :	Cam C	
Main Air pressure :	0.784	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	33	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.41	kN		
	Max ;	0.54	kN	Max Punch ;	1
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	20
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	27

Tablet Data (N/A)

Total Counter :	50010	Tablets			
A.W.C Counter :	45673	Tablets			
HEP :	38 (0.1%)	Tablets	LEP :	34 (0.1%)	Tablets
GOOD :	45601 (99.8%)	Tablets			