

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO800mg STV11C00
User ID :	vg96371	Batch NO. :	VIM2500380
Print Interval :	50000 Tablets	Running Time :	03 Hour 12 Min 07 Sec
Total Counter :	385438	Total Running Time :	507 Hour 18 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	149	%	Manual ;	35	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	23.71	kN	No		
HEP :	25.0 %	22.80	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	18.60	kN	Yes 15	Times	
Ref :		18.24	kN			
LCP :	2.0 %	17.87	kN	Yes 15	Times	
LEP :	25.0 %	13.68	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	12.77	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.80	kN	Min :	1.71	kN	Punch NO.;	18
SD :	3.00	%	Max :	1.91	kN	Punch NO.;	49
Mean Main Pressure :	18.26	kN	Min :	17.74	kN	Punch NO.;	42
SD :	1.30	%	Max :	19.00	kN	Punch NO.;	27
Filling Depth :	Increase ; 26	Times	Decrease ;	83	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	27	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.40	mm	Pre Thickness ;	4.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.77	mm	Main Thickness ;	2.78	mm
Filling Depth :	9.60	mm	Current Cam :	Cam C	
Main Air pressure :	0.807	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	65	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.29	kN		
	Max ;	0.42	kN	Max Punch ;	51
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	20
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	9

Tablet Data (N/A)

Total Counter :	385438	Tablets			
A.W.C Counter :	376657	Tablets			
HEP :	0 (0%)	Tablets	LEP :	195 (0.1%)	Tablets
GOOD :	376462 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO800mg STV11C00
User ID :	vg96371	Batch NO. :	VIM2500380
Print Interval :	50000 Tablets	Running Time :	03 Hour 12 Min 08 Sec
Total Counter :	385468	Total Running Time :	507 Hour 18 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	149	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	23.85	kN	No		
HEP :	25.0 %	22.94	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	18.72	kN	Yes 15	Times	
Ref :		18.35	kN			
LCP :	2.0 %	17.98	kN	Yes 15	Times	
LEP :	25.0 %	13.76	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	12.84	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.42	kN	Min :	2.33	kN	Punch NO.;	2
SD :	2.50	%	Max :	2.56	kN	Punch NO.;	16
Mean Main Pressure :	18.38	kN	Min :	17.62	kN	Punch NO.;	18
SD :	1.70	%	Max :	19.12	kN	Punch NO.;	27
Filling Depth :	Increase ;	28	Times	Decrease ;	22	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	27	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.40	mm	Pre Thickness ;	4.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.83	mm	Main Thickness ;	2.84	mm
Filling Depth :	10.03	mm	Current Cam :	Cam C	
Main Air pressure :	0.807	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	65	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.29	kN		
	Max ;	0.42	kN	Max Punch ;	51
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	20
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	9

Tablet Data (N/A)

Total Counter :	385468	Tablets			
A.W.C Counter :	376657	Tablets			
HEP :	0 (0%)	Tablets	LEP :	195 (0.1%)	Tablets
GOOD :	376462 (99.9%)	Tablets			