

PRODUCTION REPORT

Product Information

Machine Name : VANTIX P720D User ID : vg96371 Print Interval : 50000 Tablets Total Counter : 705242 Station : Station 1	Product Name : ACICLO800mg STV11C00 Batch NO. : VIM2500380 Running Time : 06 Hour 00 Min 46 Sec Total Running Time : 510 Hour 7 Min
--	---

Setting Value

Feeder :	Auto ;	149	%	Manual ;	35	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		750000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.03	kN	No		
HEP :	25.0 %	25.03	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	20.43	kN	Yes 15	Times	
Ref :		20.03	kN			
LCP :	2.0 %	19.62	kN	Yes 15	Times	
LEP :	25.0 %	15.02	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	14.02	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.04	kN	Min :	1.93	kN	Punch NO.;	13
		3.00	%	Max :	2.16	kN	Punch NO.;	43
Mean Main Pressure :		20.18	kN	Min :	19.35	kN	Punch NO.;	18
	SD :	1.60	%	Max :	20.98	kN	Punch NO.;	27
Filling Depth :	Increase ;	8	Times	Decrease ;	0	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	27	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.30	mm	Pre Thickness ;	4.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.64	mm	Main Thickness ;	2.65	mm
Filling Depth :	9.98	mm	Current Cam :	Cam C	
Main Air pressure :	0.621	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.25	kN		
	Max ;	0.39	kN	Max Punch ;	51
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	20
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	9

Tablet Data (N/A)

Total Counter :	705242	Tablets			
A.W.C Counter :	696238	Tablets			
HEP :	0 (0%)	Tablets	LEP :	195 (0.0%)	Tablets
GOOD :	696043 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO800mg STV11C00
User ID :	vg96371	Batch NO. :	VIM2500380
Print Interval :	50000 Tablets	Running Time :	06 Hour 00 Min 46 Sec
Total Counter :	705242	Total Running Time :	510 Hour 7 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	149	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		750000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	24.04	kN	No		
HEP :	25.0 %	23.11	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	18.86	kN	Yes	15	Times
Ref :		18.49	kN			
LCP :	2.0 %	18.12	kN	Yes	15	Times
LEP :	25.0 %	13.87	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	12.94	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.56	kN	Min :	2.45	kN	Punch NO.;	47
SD :	2.40	%	Max :	2.73	kN	Punch NO.;	16
Mean Main Pressure :	18.55	kN	Min :	17.90	kN	Punch NO.;	18
SD :	1.80	%	Max :	19.46	kN	Punch NO.;	27
Filling Depth :	Increase ;	5	Times	Decrease ;	3	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	27	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.30	mm	Pre Thickness ;	4.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.79	mm	Main Thickness ;	2.80	mm
Filling Depth :	9.93	mm	Current Cam :	Cam C	
Main Air pressure :	0.621	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.25	kN		
	Max ;	0.39	kN	Max Punch ;	51
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	20
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	9

Tablet Data (N/A)

Total Counter :	705242	Tablets			
A.W.C Counter :	696238	Tablets			
HEP :	0 (0%)	Tablets	LEP :	195 (0.0%)	Tablets
GOOD :	696043 (100.0%)	Tablets			