

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG,STV11B0
User ID :	rp98927	Batch NO. :	VIM2500340
Print Interval :	50000 Tablets	Running Time :	02 Hour 36 Min 00 Sec
Total Counter :	400218	Total Running Time :	513 Hour 2 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	75	%	Manual ;	35	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.87	kN	No		
HEP :	25.0 %	18.14	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.80	kN	Yes 15	Times	
Ref :		14.51	kN			
LCP :	2.0 %	14.22	kN	Yes 15	Times	
LEP :	25.0 %	10.88	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.16	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.19	kN	Min :	2.05	kN	Punch NO.;	22
SD :	3.10	%	Max :	2.36	kN	Punch NO.;	6
Mean Main Pressure :	14.46	kN	Min :	13.94	kN	Punch NO.;	39
SD :	1.80	%	Max :	15.14	kN	Punch NO.;	6
Filling Depth :	Increase ; 0	Times	Decrease ;	15	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.10	mm	Main Thickness ;	2.11	mm
Filling Depth :	6.69	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.700	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	22
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	14
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.10	kN	Max Punch ;	11

Tablet Data (N/A)

Total Counter :	400218	Tablets			
A.W.C Counter :	395528	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	395528 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG,STV11B0
User ID :	rp98927	Batch NO. :	VIM2500340
Print Interval :	50000 Tablets	Running Time :	02 Hour 36 Min 00 Sec
Total Counter :	400218	Total Running Time :	513 Hour 2 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	76	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.07	kN	No		
HEP :	25.0 %	19.30	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.75	kN	Yes 15	Times	
Ref :		15.44	kN			
LCP :	2.0 %	15.13	kN	Yes 15	Times	
LEP :	25.0 %	11.58	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.81	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.21	kN	Min :	2.00	kN	Punch NO.;	33
SD :	3.90	%	Max :	2.37	kN	Punch NO.;	5
Mean Main Pressure :	15.36	kN	Min :	14.71	kN	Punch NO.;	33
SD :	1.60	%	Max :	15.84	kN	Punch NO.;	46
Filling Depth :	Increase ;	0	Times	Decrease ;	1	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.20	mm	Main Thickness ;	2.21	mm
Filling Depth :	7.62	mm	Current Cam :	Cam C	
Main Air pressure :	0.700	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	1
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	14
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.10	kN	Max Punch ;	11

Tablet Data (N/A)

Total Counter :	400218	Tablets			
A.W.C Counter :	395528	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	395528 (100.0%)	Tablets			