

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG,STV11B0
User ID :	vg96371	Batch NO. :	VIM2500440
Print Interval :	50000 Tablets	Running Time :	05 Hour 28 Min 09 Sec
Total Counter :	850424	Total Running Time :	525 Hour 31 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	56	%	Manual ;	35	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.92	kN	No		
HEP :	25.0 %	18.19	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.84	kN	Yes 15	Times	
Ref :		14.55	kN			
LCP :	2.0 %	14.26	kN	Yes 15	Times	
LEP :	25.0 %	10.91	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.19	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.09	kN	Min :	1.96	kN	Punch NO.;	22
SD :	2.10	%	Max :	2.17	kN	Punch NO.;	53
Mean Main Pressure :	14.60	kN	Min :	14.14	kN	Punch NO.;	8
SD :	1.30	%	Max :	14.96	kN	Punch NO.;	46
Filling Depth :	Increase ; 5	Times	Decrease ;	34	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.10	mm	Main Thickness ;	2.11	mm
Filling Depth :	7.05	mm	Current Cam :	Cam C	
Main Air pressure :	0.808	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	27	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	20
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.14	kN	Max Punch ;	14
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	65

Tablet Data (N/A)

Total Counter :	850424	Tablets			
A.W.C Counter :	848611	Tablets			
HEP :	0 (0%)	Tablets	LEP :	4 (0.0%)	Tablets
GOOD :	848607 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG,STV11B0
User ID :	vg96371	Batch NO. :	VIM2500440
Print Interval :	50000 Tablets	Running Time :	05 Hour 28 Min 09 Sec
Total Counter :	850424	Total Running Time :	525 Hour 31 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	57	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.07	kN	No		
HEP :	25.0 %	19.30	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	15.75	kN	Yes	15	Times
Ref :		15.44	kN			
LCP :	2.0 %	15.13	kN	Yes	15	Times
LEP :	25.0 %	11.58	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	10.81	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.03	kN	Min :	1.94	kN	Punch NO.;	2
SD :	2.60	%	Max :	2.15	kN	Punch NO.;	12
Mean Main Pressure :	15.49	kN	Min :	15.12	kN	Punch NO.;	25
SD :	1.50	%	Max :	16.27	kN	Punch NO.;	52
Filling Depth :	Increase ;	13	Times	Decrease ;	11	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.97	mm	Pre Thickness ;	2.98	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.20	mm	Main Thickness ;	2.21	mm
Filling Depth :	7.58	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.808	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	27	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	23
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.14	kN	Max Punch ;	14
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	65

Tablet Data (N/A)

Total Counter :	850424	Tablets			
A.W.C Counter :	848611	Tablets			
HEP :	0 (0%)	Tablets	LEP :	4 (0.0%)	Tablets
GOOD :	848607 (100.0%)	Tablets			