

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG,STV11B0
User ID :	vg96371	Batch NO. :	VIM2500440
Print Interval :	50000 Tablets	Running Time :	08 Hour 41 Min 03 Sec
Total Counter :	1350644	Total Running Time :	528 Hour 44 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	56	%	Manual ;	35	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.92	kN	No		
HEP :	25.0 %	18.19	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.84	kN	Yes 15	Times	
Ref :		14.55	kN			
LCP :	2.0 %	14.26	kN	Yes 15	Times	
LEP :	25.0 %	10.91	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.19	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.12	kN	Min :	2.00	kN	Punch NO.;	23
SD :	2.20	%	Max :	2.21	kN	Punch NO.;	64
Mean Main Pressure :	14.61	kN	Min :	14.21	kN	Punch NO.;	21
SD :	1.20	%	Max :	15.04	kN	Punch NO.;	49
Filling Depth :	Increase ; 5	Times	Decrease ;	35	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.10	mm	Main Thickness ;	2.11	mm
Filling Depth :	7.02	mm	Current Cam :	Cam C	
Main Air pressure :	0.803	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.13	kN	Max Punch ;	14
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	13

Tablet Data (N/A)

Total Counter :	1350644	Tablets			
A.W.C Counter :	1348653	Tablets			
HEP :	0 (0%)	Tablets	LEP :	4 (0.0%)	Tablets
GOOD :	1348649 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG,STV11B0
User ID :	vg96371	Batch NO. :	VIM2500440
Print Interval :	50000 Tablets	Running Time :	08 Hour 41 Min 03 Sec
Total Counter :	1350644	Total Running Time :	528 Hour 44 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	57	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.07	kN	No		
HEP :	25.0 %	19.30	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	15.75	kN	Yes	15	Times
Ref :		15.44	kN			
LCP :	2.0 %	15.13	kN	Yes	15	Times
LEP :	25.0 %	11.58	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	10.81	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.07	kN	Min :	1.97	kN	Punch NO.;	39
SD :	2.60	%	Max :	2.24	kN	Punch NO.;	12
Mean Main Pressure :	15.62	kN	Min :	15.16	kN	Punch NO.;	39
SD :	1.70	%	Max :	16.31	kN	Punch NO.;	29
Filling Depth :	Increase ;	15	Times	Decrease ;	11	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.97	mm	Pre Thickness ;	2.98	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.20	mm	Main Thickness ;	2.21	mm
Filling Depth :	7.64	mm	Current Cam :	Cam C	
Main Air pressure :	0.803	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.13	kN	Max Punch ;	14
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	13

Tablet Data (N/A)

Total Counter :	1350644	Tablets			
A.W.C Counter :	1348653	Tablets			
HEP :	0 (0%)	Tablets	LEP :	4 (0.0%)	Tablets
GOOD :	1348649 (100.0%)	Tablets			