

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEVE135MG,STMV2 A00
User ID :	sj97904	Batch NO. :	MVM2500113
Print Interval :	50000 Tablets	Running Time :	10 Hour 39 Min 06 Sec
Total Counter :	1350582	Total Running Time :	540 Hour 18 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	62	%	Manual ;	35	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.92	kN	No		
HEP :	25.0 %	16.27	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	13.28	kN	Yes 15	Times	
Ref :		13.02	kN			
LCP :	2.0 %	12.76	kN	Yes 15	Times	
LEP :	25.0 %	9.76	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.11	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.33	kN	Min :	1.24	kN	Punch NO.;	13
SD :	3.60	%	Max :	1.46	kN	Punch NO.;	45
Mean Main Pressure :	13.11	kN	Min :	12.06	kN	Punch NO.;	32
SD :	2.90	%	Max :	13.97	kN	Punch NO.;	45
Filling Depth :	Increase ;	233	Times	Decrease ;	242	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.75	mm	Pre Thickness ;	2.76	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.69	mm	Main Thickness ;	1.69	mm
Filling Depth :	9.51	mm	Current Cam :	Cam C	
Main Air pressure :	0.806	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.16	kN	Max Punch ;	52
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.13	kN	Max Punch ;	37
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	1350582	Tablets			
A.W.C Counter :	1342941	Tablets			
HEP :	0 (0%)	Tablets	LEP :	131 (0.0%)	Tablets
GOOD :	1342810 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEVE135MG,STMV2 A00
User ID :	sj97904	Batch NO. :	MVM2500113
Print Interval :	50000 Tablets	Running Time :	10 Hour 39 Min 06 Sec
Total Counter :	1350582	Total Running Time :	540 Hour 18 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	54	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.64	kN	No		
HEP :	25.0 %	16.96	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	13.84	kN	Yes 15	Times	
Ref :		13.57	kN			
LCP :	2.0 %	13.30	kN	Yes 15	Times	
LEP :	25.0 %	10.17	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.50	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.28	kN	Min :	1.20	kN	Punch NO.;	27
SD :	2.90	%	Max :	1.37	kN	Punch NO.;	32
Mean Main Pressure :	13.78	kN	Min :	13.17	kN	Punch NO.;	18
SD :	2.30	%	Max :	14.67	kN	Punch NO.;	49
Filling Depth :	Increase ;	78	Times	Decrease ;	79	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	2.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.82	mm	Main Thickness ;	1.83	mm
Filling Depth :	8.46	mm	Current Cam :	Cam C	
Main Air pressure :	0.806	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.17	kN	Max Punch ;	1
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.13	kN	Max Punch ;	37
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	1350582	Tablets			
A.W.C Counter :	1342941	Tablets			
HEP :	0 (0%)	Tablets	LEP :	131 (0.0%)	Tablets
GOOD :	1342810 (100.0%)	Tablets			