

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                       |
|------------------|---------------|----------------------|-----------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MEBEVE135MG,STMV2 A00 |
| User ID :        | yu98249       | Batch NO. :          | MVM2500113            |
| Print Interval : | 50000 Tablets | Running Time :       | 14 Hour 36 Min 00 Sec |
| Total Counter :  | 1850748       | Total Running Time : | 544 Hour 15 Min       |
| Station :        | Station 1     |                      |                       |

### Setting Value

|                                    |             |          |         |                    |              |           |
|------------------------------------|-------------|----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 65       | %       | Manual ;           | 35           | RPM       |
| Filling Cam :                      |             | Cam C    |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |             | 8.5-14mm |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |             | 2000000  | Tablets |                    |              |           |
| Air Pressure Low Limit :           |             | 0.400    | MPa     |                    |              |           |
| Oil Lubrication :                  |             |          |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 30       | Min     | Supply Time ;      | 0.5          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 20       | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |             | 5.0      | Sec     |                    |              |           |
| Initial Reject Time :              |             | 2        | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 1.00     | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 1.00     | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 1.00     | kN      |                    |              |           |
|                                    |             |          |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 %      | 16.69    | kN      | No                 |              |           |
| HEP :                              | 22.0 %      | 15.66    | kN      | Yes 10             | Rotations 10 | Tablets   |
| HCP :                              | 2.0 %       | 13.09    | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 12.84    | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 12.58    | kN      | Yes 15             | Times        |           |
| LEP :                              | 22.0 %      | 10.01    | kN      | Yes 10             | Rotations 10 | Tablets   |
| LSP :                              | 30.0 %      | 8.99     | kN      | No                 |              |           |
| SD limit :                         | 20.0 %      |          |         | Yes                |              |           |
| Pre HSP                            |             | 20.00    | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |          |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | None        |          |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 1.41       | kN  | Min : | 1.27       | kN  | Punch NO.; | 53 |
| SD :                 | 4.50       | %   | Max : | 1.54       | kN  | Punch NO.; | 4  |
| Mean Main Pressure : | 12.97      | kN  | Min : | 12.24      | kN  | Punch NO.; | 15 |
| SD :                 | 2.70       | %   | Max : | 13.87      | kN  | Punch NO.; | 23 |
| Filling Depth :      | Increase ; | 389 | Times | Decrease ; | 400 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 20      | RPM | Capacity :       | 127200   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 13       | RPM          |
| Pre Upper Punch Position ;    | 2.50    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.21    | mm  | Pre Thickness ;  | 2.71     | mm           |
| Main Upper Punch Position ;   | 2.20    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 3.89    | mm  | Main Thickness ; | 1.69     | mm           |
| Filling Depth :               | 9.52    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.821   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 4       | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 11      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.17 | kN |             |    |
|                  | Max ;     | 0.28 | kN | Max Punch ; | 51 |
| Lower Punch :    | Average ; | 0.11 | kN |             |    |
|                  | Max ;     | 0.12 | kN | Max Punch ; | 36 |
| Ejection Force : | Average ; | 0.05 | kN |             |    |
|                  | Max ;     | 0.06 | kN | Max Punch ; | 4  |

### Tablet Data (N/A)

|                 |                     |         |       |            |         |
|-----------------|---------------------|---------|-------|------------|---------|
| Total Counter : | 1850748             | Tablets |       |            |         |
| A.W.C Counter : | 1839276             | Tablets |       |            |         |
| HEP :           | 9 (0.0%)            | Tablets | LEP : | 573 (0.0%) | Tablets |
| GOOD :          | 1838694<br>(100.0%) | Tablets |       |            |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                       |
|------------------|---------------|----------------------|-----------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MEBEVE135MG,STMV2 A00 |
| User ID :        | yu98249       | Batch NO. :          | MVM2500113            |
| Print Interval : | 50000 Tablets | Running Time :       | 14 Hour 36 Min 00 Sec |
| Total Counter :  | 1850748       | Total Running Time : | 544 Hour 15 Min       |
| Station :        | Station 2     |                      |                       |

### Setting Value

|                                    |        |           |         |                    |              |           |
|------------------------------------|--------|-----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 64        | %       | Manual ;           | 20           | RPM       |
| Filling Cam :                      |        | Cam C     |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |        | 8.5-14mm  |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |        | 2000000   | Tablets |                    |              |           |
| Air Pressure Low Limit :           |        | 0.400     | MPa     |                    |              |           |
| Oil Lubrication :                  |        |           |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 30        | Min     | Supply Time ;      | 0.5          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 20        | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |        | 5.0       | Sec     |                    |              |           |
| Initial Reject Time :              |        | 2         | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 1.00      | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 1.00      | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 1.00      | kN      |                    |              |           |
|                                    |        |           |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 % | 17.44     | kN      | No                 |              |           |
| HEP :                              | 22.0 % | 16.37     | kN      | Yes 10             | Rotations 10 | Tablets   |
| HCP :                              | 2.0 %  | 13.68     | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 13.41     | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 13.15     | kN      | Yes 15             | Times        |           |
| LEP :                              | 22.0 % | 10.46     | kN      | Yes 10             | Rotations 10 | Tablets   |
| LSP :                              | 30.0 % | 9.39      | kN      | No                 |              |           |
| SD limit :                         | 20.0 % |           |         | Yes                |              |           |
| Pre HSP                            |        | 20.00     | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | N      |           |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 1.38       | kN  | Min : | 1.26       | kN  | Punch NO.; | 13 |
| SD :                 | 4.40       | %   | Max : | 1.54       | kN  | Punch NO.; | 43 |
| Mean Main Pressure : | 13.43      | kN  | Min : | 12.83      | kN  | Punch NO.; | 41 |
| SD :                 | 2.20       | %   | Max : | 14.06      | kN  | Punch NO.; | 50 |
| Filling Depth :      | Increase ; | 150 | Times | Decrease ; | 146 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 20      | RPM | Capacity :       | 127200   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 13       | RPM          |
| Pre Upper Punch Position ;    | 2.50    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.21    | mm  | Pre Thickness ;  | 2.71     | mm           |
| Main Upper Punch Position ;   | 2.20    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 4.03    | mm  | Main Thickness ; | 1.83     | mm           |
| Filling Depth :               | 8.54    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.821   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 4       | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 11      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.17 | kN |             |    |
|                  | Max ;     | 0.28 | kN | Max Punch ; | 51 |
| Lower Punch :    | Average ; | 0.11 | kN |             |    |
|                  | Max ;     | 0.12 | kN | Max Punch ; | 36 |
| Ejection Force : | Average ; | 0.05 | kN |             |    |
|                  | Max ;     | 0.06 | kN | Max Punch ; | 4  |

### Tablet Data (N/A)

|                 |                     |         |       |            |         |
|-----------------|---------------------|---------|-------|------------|---------|
| Total Counter : | 1850748             | Tablets |       |            |         |
| A.W.C Counter : | 1839276             | Tablets |       |            |         |
| HEP :           | 9 (0.0%)            | Tablets | LEP : | 573 (0.0%) | Tablets |
| GOOD :          | 1838694<br>(100.0%) | Tablets |       |            |         |