

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEVE135MG STMV2A00
User ID :	sj97904	Batch NO. :	MVM2500213
Print Interval :	50000 Tablets	Running Time :	15 Hour 29 Min 29 Sec
Total Counter :	1966592	Total Running Time :	560 Hour 37 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	82	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.43	kN	No		
HEP :	22.0 %	13.54	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	11.32	kN	Yes 15	Times	
Ref :		11.10	kN			
LCP :	2.0 %	10.88	kN	Yes 15	Times	
LEP :	22.0 %	8.66	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	7.77	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.64	kN	Min :	1.57	kN	Punch NO.;	13
SD :	1.80	%	Max :	1.72	kN	Punch NO.;	28
Mean Main Pressure :	10.17	kN	Min :	9.58	kN	Punch NO.;	2
SD :	2.70	%	Max :	10.81	kN	Punch NO.;	16
Filling Depth :	Increase ;	1031	Times	Decrease ;	947	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Manual		Speed ;	20	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.65	mm	Pre Thickness ;	3.15	mm
Main Upper Punch Position ;	2.20	mm			
Main Lower Punch Position ;	4.03	mm	Main Thickness ;	1.83	mm
Filling Depth :	9.49	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.800	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.21	kN		
	Max ;	0.26	kN	Max Punch ;	52
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.13	kN	Max Punch ;	27
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	1966592	Tablets			
A.W.C Counter :	1958324	Tablets			
HEP :	168 (0.0%)	Tablets	LEP :	2 (0.0%)	Tablets
GOOD :	1958154 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEVE135MG STMV2A00
User ID :	sj97904	Batch NO. :	MVM2500213
Print Interval :	50000 Tablets	Running Time :	15 Hour 29 Min 29 Sec
Total Counter :	1966592	Total Running Time :	560 Hour 37 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.92	kN	No		
HEP :	22.0 %	15.88	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	13.27	kN	Yes 15	Times	
Ref :		13.01	kN			
LCP :	2.0 %	12.75	kN	Yes 15	Times	
LEP :	22.0 %	10.15	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.11	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.32	kN	Min :	1.23	kN	Punch NO.;	38
SD :	3.00	%	Max :	1.42	kN	Punch NO.;	5
Mean Main Pressure :	11.21	kN	Min :	10.25	kN	Punch NO.;	17
SD :	3.90	%	Max :	12.18	kN	Punch NO.;	50
Filling Depth :	Increase ;	637	Times	Decrease ;	606	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.65	mm	Pre Thickness ;	3.15	mm
Main Upper Punch Position ;	2.20	mm			
Main Lower Punch Position ;	4.08	mm	Main Thickness ;	1.88	mm
Filling Depth :	8.69	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.800	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.21	kN		
	Max ;	0.30	kN	Max Punch ;	53
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.13	kN	Max Punch ;	27
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	1966592	Tablets			
A.W.C Counter :	1958324	Tablets			
HEP :	168 (0.0%)	Tablets	LEP :	2 (0.0%)	Tablets
GOOD :	1958154 (100.0%)	Tablets			