

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA 50 MG,STSH4A00
User ID :	pb97604	Batch NO. :	SHM2500350
Print Interval :	50000 Tablets	Running Time :	00 Hour 12 Min 07 Sec
Total Counter :	50052	Total Running Time :	610 Hour 8 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	33	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.90	kN	No		
HEP :	25.0 %	14.32	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.69	kN	Yes 15	Times	
Ref :		11.46	kN			
LCP :	2.0 %	11.23	kN	Yes 15	Times	
LEP :	25.0 %	8.59	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.02	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.06	kN	Min :	1.01	kN	Punch NO.;	16
		1.80	%	Max :	1.12	kN	Punch NO.;	58
Mean Main Pressure :		11.70	kN	Min :	10.92	kN	Punch NO.;	5
	SD :	3.40	%	Max :	12.69	kN	Punch NO.;	1
Filling Depth :	Increase ;	20	Times	Decrease ;	23	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.47	mm	Main Thickness ;	1.47	mm
Filling Depth :	5.09	mm	Current Cam :	Cam B	
Main Air pressure :	0.788	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	14
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.17	kN	Max Punch ;	56
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.12	kN	Max Punch ;	61

Tablet Data (N/A)

Total Counter :	50052	Tablets			
A.W.C Counter :	46671	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	46671 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA 50 MG,STSH4A00
User ID :	pb97604	Batch NO. :	SHM2500350
Print Interval :	50000 Tablets	Running Time :	00 Hour 12 Min 07 Sec
Total Counter :	50052	Total Running Time :	610 Hour 8 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	30	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.51	kN	No		
HEP :	25.0 %	15.87	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.95	kN	Yes 15	Times	
Ref :		12.70	kN			
LCP :	2.0 %	12.44	kN	Yes 15	Times	
LEP :	25.0 %	9.52	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.89	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.10	kN	Min :	1.04	kN	Punch NO.;	16
SD :	2.10	%	Max :	1.16	kN	Punch NO.;	60
Mean Main Pressure :	12.62	kN	Min :	11.88	kN	Punch NO.;	16
SD :	2.90	%	Max :	13.66	kN	Punch NO.;	3
Filling Depth :	Increase ;	14	Times	Decrease ;	16	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	2.70	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.60	mm	Main Thickness ;	1.60	mm
Filling Depth :	5.25	mm	Current Cam :	Cam B	
Main Air pressure :	0.788	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	14
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.17	kN	Max Punch ;	56
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.12	kN	Max Punch ;	61

Tablet Data (N/A)

Total Counter :	50052	Tablets			
A.W.C Counter :	46671	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	46671 (100.0%)	Tablets			