

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA 50 MG,STSH4A00
User ID :	pb97604	Batch NO. :	SHM2500350
Print Interval :	50000 Tablets	Running Time :	01 Hour 10 Min 11 Sec
Total Counter :	300282	Total Running Time :	611 Hour 6 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	33	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.05	kN	No		
HEP :	25.0 %	15.44	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	12.60	kN	Yes	15	Times
Ref :		12.35	kN			
LCP :	2.0 %	12.10	kN	Yes	15	Times
LEP :	25.0 %	9.26	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	8.64	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.01	kN	Min :	0.95	kN	Punch NO.;	17
SD :	1.70	%	Max :	1.04	kN	Punch NO.;	58
Mean Main Pressure :	12.31	kN	Min :	11.48	kN	Punch NO.;	74
SD :	3.30	%	Max :	13.40	kN	Punch NO.;	7
Filling Depth :	Increase ;	25	Times	Decrease ;	54	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.44	mm	Main Thickness ;	1.44	mm
Filling Depth :	4.83	mm	Current Cam :	Cam B	
Main Air pressure :	0.800	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.27	kN		
	Max ;	0.35	kN	Max Punch ;	74
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.20	kN	Max Punch ;	62
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.09	kN	Max Punch ;	57

Tablet Data (N/A)

Total Counter :	300282	Tablets			
A.W.C Counter :	296921	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	296921 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA 50 MG,STSH4A00
User ID :	pb97604	Batch NO. :	SHM2500350
Print Interval :	50000 Tablets	Running Time :	01 Hour 10 Min 11 Sec
Total Counter :	300282	Total Running Time :	611 Hour 6 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	30	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.38	kN	No		
HEP :	25.0 %	16.71	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.64	kN	Yes 15	Times	
Ref :		13.37	kN			
LCP :	2.0 %	13.10	kN	Yes 15	Times	
LEP :	25.0 %	10.03	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.36	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.09	kN	Min :	1.04	kN	Punch NO.;	21
SD :	1.70	%	Max :	1.14	kN	Punch NO.;	33
Mean Main Pressure :	13.32	kN	Min :	12.65	kN	Punch NO.;	5
SD :	2.30	%	Max :	13.93	kN	Punch NO.;	7
Filling Depth :	Increase ;	20	Times	Decrease ;	29	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	2.70	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.57	mm	Main Thickness ;	1.57	mm
Filling Depth :	5.10	mm	Current Cam :	Cam B	
Main Air pressure :	0.800	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.28	kN		
	Max ;	0.37	kN	Max Punch ;	23
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.20	kN	Max Punch ;	62
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.09	kN	Max Punch ;	57

Tablet Data (N/A)

Total Counter :	300282	Tablets			
A.W.C Counter :	296921	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	296921 (100.0%)	Tablets			