

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA 50 MG,STSH4A00
User ID :	sj97904	Batch NO. :	SHM2500350
Print Interval :	50000 Tablets	Running Time :	04 Hour 15 Min 44 Sec
Total Counter :	1100850	Total Running Time :	614 Hour 12 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	21	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.37	kN	No		
HEP :	25.0 %	16.70	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.63	kN	Yes 15	Times	
Ref :		13.36	kN			
LCP :	2.0 %	13.10	kN	Yes 15	Times	
LEP :	25.0 %	10.02	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.35	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.92	kN	Min :	0.87	kN	Punch NO.;	10
SD :	2.20	%	Max :	0.97	kN	Punch NO.;	54
Mean Main Pressure :	13.53	kN	Min :	12.26	kN	Punch NO.;	10
SD :	4.00	%	Max :	15.22	kN	Punch NO.;	76
Filling Depth :	Increase ;	84	Times	Decrease ;	136	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.44	mm	Main Thickness ;	1.44	mm
Filling Depth :	5.13	mm	Current Cam :	Cam B	
Main Air pressure :	0.786	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.20	kN	Max Punch ;	62
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	62
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	61

Tablet Data (N/A)

Total Counter :	1100850	Tablets			
A.W.C Counter :	1097407	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1097405 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA 50 MG,STSH4A00
User ID :	sj97904	Batch NO. :	SHM2500350
Print Interval :	50000 Tablets	Running Time :	04 Hour 15 Min 44 Sec
Total Counter :	1100850	Total Running Time :	614 Hour 12 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	23	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.50	kN	No		
HEP :	25.0 %	17.79	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	14.52	kN	Yes	15	Times
Ref :		14.23	kN			
LCP :	2.0 %	13.95	kN	Yes	15	Times
LEP :	25.0 %	10.67	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.96	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.02	kN	Min :	0.98	kN	Punch NO.;	27
		2.00	%	Max :	1.09	kN	Punch NO.;	35
Mean Main Pressure :		14.23	kN	Min :	13.24	kN	Punch NO.;	19
	SD :	3.90	%	Max :	16.03	kN	Punch NO.;	35
Filling Depth :	Increase ;	55	Times	Decrease ;	70	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	2.70	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.57	mm	Main Thickness ;	1.57	mm
Filling Depth :	5.40	mm	Current Cam :	Cam B	
Main Air pressure :	0.786	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.20	kN	Max Punch ;	62
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	62
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	61

Tablet Data (N/A)

Total Counter :	1100850	Tablets			
A.W.C Counter :	1097407	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1097405 (100.0%)	Tablets			