

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA 50 MG,STSH4A00
User ID :	dm98328	Batch NO. :	SHM2500350
Print Interval :	50000 Tablets	Running Time :	22 Hour 39 Min 35 Sec
Total Counter :	5868998	Total Running Time :	632 Hour 37 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	22	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.08	kN	No		
HEP :	25.0 %	17.38	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	14.18	kN	Yes	15	Times
Ref :		13.90	kN			
LCP :	2.0 %	13.63	kN	Yes	15	Times
LEP :	25.0 %	10.43	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.73	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.10	kN	Min :	1.07	kN	Punch NO.;	10
SD :	2.00	%	Max :	1.18	kN	Punch NO.;	76
Mean Main Pressure :	13.78	kN	Min :	12.58	kN	Punch NO.;	70
SD :	4.90	%	Max :	16.13	kN	Punch NO.;	76
Filling Depth :	Increase ;	409	Times	Decrease ;	443	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.51	mm	Main Thickness ;	1.52	mm
Filling Depth :	5.29	mm	Current Cam :	Cam B	
Main Air pressure :	0.792	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.23	kN	Max Punch ;	29
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	62
Ejection Force :	Average ;	0.10	kN		
	Max ;	0.16	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	5868998	Tablets			
A.W.C Counter :	5864390	Tablets			
HEP :	254 (0.0%)	Tablets	LEP :	99 (0.0%)	Tablets
GOOD :	5864037 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA 50 MG,STSH4A00
User ID :	dm98328	Batch NO. :	SHM2500350
Print Interval :	50000 Tablets	Running Time :	22 Hour 39 Min 35 Sec
Total Counter :	5868998	Total Running Time :	632 Hour 37 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.10	kN	No		
HEP :	25.0 %	18.36	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	14.99	kN	Yes	15	Times
Ref :		14.69	kN			
LCP :	2.0 %	14.40	kN	Yes	15	Times
LEP :	25.0 %	11.02	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	10.28	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.21	kN	Min :	1.14	kN	Punch NO.;	9
SD :	2.70	%	Max :	1.32	kN	Punch NO.;	76
Mean Main Pressure :	14.40	kN	Min :	12.72	kN	Punch NO.;	17
SD :	6.00	%	Max :	17.65	kN	Punch NO.;	76
Filling Depth :	Increase ;	187	Times	Decrease ;	224	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	2.71	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.64	mm	Main Thickness ;	1.64	mm
Filling Depth :	5.66	mm	Current Cam :	Cam B	
Main Air pressure :	0.792	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.23	kN	Max Punch ;	29
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	62
Ejection Force :	Average ;	0.10	kN		
	Max ;	0.16	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	5868998	Tablets			
A.W.C Counter :	5864390	Tablets			
HEP :	254 (0.0%)	Tablets	LEP :	99 (0.0%)	Tablets
GOOD :	5864037 (100.0%)	Tablets			