

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET1000mg STYQ1A00
User ID :	pb97604	Batch NO. :	YQM2501110
Print Interval :	50000 Tablets	Running Time :	04 Hour 44 Min 07 Sec
Total Counter :	600260	Total Running Time :	678 Hour 54 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	40	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2250000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.60	kN	No		
HEP :	25.0 %	26.54	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	21.65	kN	Yes 15	Times	
Ref :		21.23	kN			
LCP :	2.0 %	20.80	kN	Yes 15	Times	
LEP :	25.0 %	15.92	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	14.86	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.24	kN	Min :	3.03	kN	Punch NO.;	3
		3.40	%	Max :	3.46	kN	Punch NO.;	32
Mean Main Pressure :		21.41	kN	Min :	20.39	kN	Punch NO.;	48
	SD :	2.70	%	Max :	22.56	kN	Punch NO.;	23
Filling Depth :	Increase ;	40	Times	Decrease ;	43	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.70	mm	Pre Thickness ;	4.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.64	mm	Main Thickness ;	3.65	mm
Filling Depth :	9.20	mm	Current Cam :	Cam C	
Main Air pressure :	0.804	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	12
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.16	kN	Max Punch ;	39

Tablet Data (N/A)

Total Counter :	600260	Tablets			
A.W.C Counter :	598406	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	598404 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET1000mg STYQ1A00
User ID :	pb97604	Batch NO. :	YQM2501110
Print Interval :	50000 Tablets	Running Time :	04 Hour 44 Min 07 Sec
Total Counter :	600260	Total Running Time :	678 Hour 54 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	40	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2250000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.80	kN	No		
HEP :	25.0 %	28.66	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	23.38	kN	Yes 15	Times	
Ref :		22.93	kN			
LCP :	2.0 %	22.47	kN	Yes 15	Times	
LEP :	25.0 %	17.19	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	16.05	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.27	kN	Min :	3.02	kN	Punch NO.;	31
		4.60	%	Max :	3.67	kN	Punch NO.;	22
Mean Main Pressure :		23.17	kN	Min :	21.82	kN	Punch NO.;	31
	SD :	3.60	%	Max :	25.00	kN	Punch NO.;	22
Filling Depth :	Increase ;	24	Times	Decrease ;	31	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.70	mm	Pre Thickness ;	4.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.64	mm	Main Thickness ;	3.65	mm
Filling Depth :	9.39	mm	Current Cam :	Cam C	
				8.5-14mm	
Main Air pressure :	0.804	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	12
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.16	kN	Max Punch ;	39

Tablet Data (N/A)

Total Counter :	600260	Tablets			
A.W.C Counter :	598406	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	598404 (100.0%)	Tablets			