

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO400MG STIU2B00
User ID :	pb97604	Batch NO. :	IUM2500140
Print Interval :	50000 Tablets	Running Time :	02 Hour 22 Min 42 Sec
Total Counter :	350118	Total Running Time :	712 Hour 16 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	195	%	Manual ;	66	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	24.00	kN	No		
HEP :	25.0 %	23.07	kN	Yes 10	Rotations 15	Tablets
HCP :	3.0 %	19.01	kN	Yes 15	Times	
Ref :		18.46	kN			
LCP :	3.0 %	17.91	kN	Yes 15	Times	
LEP :	25.0 %	13.84	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	12.92	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.53	kN	Min :	0.48	kN	Punch NO.;	38
SD :	3.20	%	Max :	0.57	kN	Punch NO.;	41
Mean Main Pressure :	17.59	kN	Min :	16.18	kN	Punch NO.;	2
SD :	4.40	%	Max :	19.09	kN	Punch NO.;	35
Filling Depth :	Increase ;	614	Times	Decrease ;	599	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	49	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.70	mm	Pre Thickness ;	3.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	1.51	mm
Filling Depth :	7.46	mm	Current Cam :	Cam C	
Main Air pressure :	0.795	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	52	Min			
Lower Punch Remain Time (S2):	22	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.28	kN	Max Punch ;	46
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.07	kN	Max Punch ;	49

Tablet Data (N/A)

Total Counter :	350118	Tablets			
A.W.C Counter :	337301	Tablets			
HEP :	47 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	337254 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO400MG STIU2B00
User ID :	pb97604	Batch NO. :	IUM2500140
Print Interval :	50000 Tablets	Running Time :	02 Hour 22 Min 42 Sec
Total Counter :	350144	Total Running Time :	712 Hour 16 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	74	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.91	kN	No		
HEP :	25.0 %	24.91	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	20.33	kN	Yes 15	Times	
Ref :		19.93	kN			
LCP :	2.0 %	19.53	kN	Yes 15	Times	
LEP :	25.0 %	14.95	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	13.95	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.72	kN	Min :	0.69	kN	Punch NO.;	38
SD :	2.10	%	Max :	0.76	kN	Punch NO.;	1
Mean Main Pressure :	20.13	kN	Min :	18.90	kN	Punch NO.;	13
SD :	3.40	%	Max :	22.23	kN	Punch NO.;	53
Filling Depth :	Increase ;	316	Times	Decrease ;	331	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	50	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.70	mm	Pre Thickness ;	3.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.55	mm	Main Thickness ;	1.56	mm
Filling Depth :	7.06	mm	Current Cam :	Cam C	
Main Air pressure :	0.797	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	52	Min			
Lower Punch Remain Time (S2):	22	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.28	kN	Max Punch ;	46
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.07	kN	Max Punch ;	49

Tablet Data (N/A)

Total Counter :	350144	Tablets			
A.W.C Counter :	337301	Tablets			
HEP :	47 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	337254 (100.0%)	Tablets			