

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO400MG STIU2B00
User ID :	kp97154	Batch NO. :	IUM2500140
Print Interval :	50000 Tablets	Running Time :	09 Hour 38 Min 10 Sec
Total Counter :	1400528	Total Running Time :	719 Hour 32 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	105	%	Manual ;	66	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.39	kN	No		
HEP :	25.0 %	24.41	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	19.92	kN	Yes 15	Times	
Ref :		19.53	kN			
LCP :	2.0 %	19.14	kN	Yes 15	Times	
LEP :	25.0 %	14.65	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	13.67	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.61	kN	Min :	0.57	kN	Punch NO.;	2
SD :	3.90	%	Max :	0.73	kN	Punch NO.;	19
Mean Main Pressure :	19.55	kN	Min :	17.80	kN	Punch NO.;	26
SD :	3.80	%	Max :	20.94	kN	Punch NO.;	33
Filling Depth :	Increase ;	1219	Times	Decrease ;	1237	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	21	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.70	mm	Pre Thickness ;	3.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	1.51	mm
Filling Depth :	6.69	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.727	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	51	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	37
Lower Punch :	Average ;	0.20	kN		
	Max ;	1.39	kN	Max Punch ;	18
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	49

Tablet Data (N/A)

Total Counter :	1400528	Tablets			
A.W.C Counter :	1377395	Tablets			
HEP :	954 (0.1%)	Tablets	LEP :	563 (0.0%)	Tablets
GOOD :	1375878 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO400MG STIU2B00
User ID :	kp97154	Batch NO. :	IUM2500140
Print Interval :	50000 Tablets	Running Time :	09 Hour 38 Min 10 Sec
Total Counter :	1400528	Total Running Time :	719 Hour 32 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	126	%	Manual ;	74	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.70	kN	No		
HEP :	25.0 %	25.67	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	20.95	kN	Yes 15	Times	
Ref :		20.54	kN			
LCP :	2.0 %	20.13	kN	Yes 15	Times	
LEP :	25.0 %	15.40	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	14.38	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.78	kN	Min :	0.73	kN	Punch NO.;	3
SD :	2.70	%	Max :	0.85	kN	Punch NO.;	49
Mean Main Pressure :	20.50	kN	Min :	18.40	kN	Punch NO.;	19
SD :	3.70	%	Max :	22.67	kN	Punch NO.;	49
Filling Depth :	Increase ;	784	Times	Decrease ;	757	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.70	mm	Pre Thickness ;	3.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.55	mm	Main Thickness ;	1.56	mm
Filling Depth :	7.22	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.727	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	51	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	37
Lower Punch :	Average ;	0.19	kN		
	Max ;	1.40	kN	Max Punch ;	18
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	49

Tablet Data (N/A)

Total Counter :	1400528	Tablets			
A.W.C Counter :	1377395	Tablets			
HEP :	954 (0.1%)	Tablets	LEP :	563 (0.0%)	Tablets
GOOD :	1375878 (99.9%)	Tablets			